

**INDUSTRIAL COMPONENT DATA**

# 3SE5122-0MA00-1CA0 SIEMENS Basic switch for position switch 3SE5112 Metal enclosure 56 mm increased corrosio..

Brand: SIEMENS | Manufacturer Part Number: 3SE5122-0MA00-1CA0



|                 |                    |
|-----------------|--------------------|
| Manufacturer    | SIEMENS            |
| MPN / Reference | 3SE5122-0MA00-1CA0 |
| Catalog number  | 51220              |
| Category        | End switch         |
| Minimum order   | 1 Pcs              |
| Document ID     | EO-D4DDDD85D3      |
| Generated       | 2026-08-02         |

## Product Overview

Basic switch for position switch 3SE5112 Metal enclosure 56 mm increased corrosion protection (increased corrosion protection) 3x (M20x 1.5) 1 NO/2 NC slow-action contacts with make-before-break without actuator head . INTERRU. POSITION 3SE51, METAL BOX, ACCORDING TO EN50041 1X(M20X1,5) CONTACTS NORMAL ACTION 1NA/NC WITHOUT ACTUATOR HEAD. Manufactured to order. Non-Cancelable Non-Returnable.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

## Additional Product Information

**Technical data**

Basic switch for position switch 3SE5112 Metal enclosure 56 mm increased corrosion protection (increased corrosion protection) 3x (M20x 1.5) 1 NO/2 NC slow-action contacts with make-before-break without actuator head

product brand name SIRIUS

product designation Mechanical safety switches

product type designation 3SE5

manufacturer's article number

? of the supplied switching contacts 3SE5000-0MA00

? of the supplied empty enclosure with cover 3SE5122-0AA00-1CA0

suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 250 V

degree of pollution class 3

surge voltage resistance rated value 4 kV

protection class IP IP66/IP67

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 15 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 10 000 000

Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 6 000

thermal current 10 A

reference code according to IEC 81346-2 B

continuous current of the C characteristic MCB 1 A; for a short-circuit current smaller than 400 A

continuous current of the quick DIAZED fuse link 10 A; for a short-circuit current smaller than 400 A

continuous current of the DI...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5122-0MA00-1CA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.