

INDUSTRIAL COMPONENT DATA

3SE5132-0CC03 SIEMENS Position switch Plastic enclosure 40 mm according to EN 50041 Device connection 1 x (M..

Brand: SIEMENS | Manufacturer Part Number: 3SE5132-0CC03



Manufacturer	SIEMENS
MPN / Reference	3SE5132-0CC03
Catalog number	51320
Category	End switch
Minimum order	1 Pcs
Document ID	EO-37383131DD
Generated	2026-08-03

Product Overview

Position switch Plastic enclosure 40 mm according to EN 50041 Device connection 1 x (M20 x 1.5) 1 NO/1 NC quick action contacts Rounded plunger made of plastic
SIRIUS POSITION SWITCH PLASTIC BOX 40MM, ACCORDING EN50041 INTEGRATED CONNECTION 1X (M20X1.5)
CONTACTS NORMAL ACTION 1NA/1NC REINFORCED PLASTIC SHANK.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

Position switch Plastic enclosure 40 mm according to EN 50041 Device connection 1 x (M20 x 1.5) 1 NO/1 NC quick action contacts Rounded plunger made of plastic
product brand name SIRIUS
product designation Mechanical position switches
product type designation 3SE5
manufacturer's article number
? of the supplied basic switch 3SE5132-0CA00
? of the supplied actuator head for position switches 3SE5000-0AC03
? of the supplied switching contacts 3SE5000-0CA00
? of the supplied empty enclosure with cover 3SE5132-0AA00
suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 400 V

degree of pollution class 3

surge voltage resistance rated value 6 kV

protection class IP IP66/IP67

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 15 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 10 000 000

Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 6 000

thermal current 10 A

material of the enclosure of the switch head plastic

reference code according to IEC 81346-2 B

continuous current of the C characteristic MCB 1 A; for a short-circuit current smaller than 400 A

continuous current of th...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5132-0CC03 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.