

INDUSTRIAL COMPONENT DATA

3SE5132-0CJ50 SIEMENS Position switch Plastic enclosure 40 mm Twist lever, adjustable length Metal lever wit..

Brand: SIEMENS | Manufacturer Part Number: 3SE5132-0CJ50



Manufacturer	SIEMENS
MPN / Reference	3SE5132-0CJ50
Catalog number	51320
Category	End switch
Minimum order	1 Pcs
Document ID	EO-3B341E61C0
Generated	2026-08-06

Product Overview

Position switch Plastic enclosure 40 mm Twist lever, adjustable length Metal lever with plastic roller 19 mm according to EN 50041 Device connection 1 x (M20 x 1.5) 1 NO/1 NC quick action contacts Rotary actuator right/left adjustable SIRIUS POSITION SWITCH PLASTIC BOX 40MM ADJUSTABLE ROTATING LEVER METAL LEVER WITH 19MM PLASTIC ROLLER ACCORDING TO EN50041 INTEGRATED CONNECTION 1X(M20X1,5) SUDDEN ACTION CONTACTS 1NA/1NC ACTION. TWIST LEVER. ADJUSTABLE RIGHT/IZD.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

Position switch Plastic enclosure 40 mm Twist lever, adjustable length Metal lever with plastic roller 19 mm according to EN 50041 Device connection 1 x (M20 x 1.5) 1 NO/1 NC quick action contacts Rotary actuator right/left adjustable product brand name SIRIUS product designation Mechanical position switches product type designation 3SE5 manufacturer's article number ? of the supplied basic switch 3SE5132-0CA00 ? of the supplied actuator head for position switches 3SE5000-0AH00 ? of the supplied operating lever 3SE5000-0AA50 ? of the supplied switching contacts 3SE5000-0CA00

? of the supplied empty enclosure with cover 3SE5132-0AA00

suitability for use safety switch No

General technical data

product function positive opening No

insulation voltage rated value 400 V

degree of pollution class 3

surge voltage resistance rated value 6 kV

protection class IP IP66/IP67

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 15 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 10 000 000

Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 6 000

thermal current 10 A

material of the enclosure of the switch head plastic

reference code according to IEC 81346-2 B

CO...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5132-0CJ50 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.