

## INDUSTRIAL COMPONENT DATA

# 3SE5162-0BA00 SIEMENS Basic switch for position switch 3SE5162 Metal enclosure XL, 56 mm wide Device connect..

Brand: SIEMENS | Manufacturer Part Number: 3SE5162-0BA00



|                 |               |
|-----------------|---------------|
| Manufacturer    | SIEMENS       |
| MPN / Reference | 3SE5162-0BA00 |
| Catalog number  | 51620         |
| Category        | End switch    |
| Minimum order   | 1 Pcs         |
| Document ID     | EO-BA9214C149 |
| Generated       | 2026-08-02    |

## Product Overview

Basic switch for position switch 3SE5162 Metal enclosure XL, 56 mm wide Device connection 3x(M20 x 1.5) IP66/IP67 2 x (1 NO/2 NC) Slow-action contacts without actuator head

BASIC SWITCH FOR POSITION SWITCH 3SE5162, METAL ENCLOSURE XL, 56MM WIDE DEVICE CONNECTION 3X(M20X1.5), IP66/IP67 2X (1NO/1NC) SLOW-ACTION CONTACT WITHOUT ACTUATOR HEAD.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

## Additional Product Information

## Technical data

Basic switch for position switch 3SE5162 Metal enclosure XL, 56 mm wide Device connection 3x(M20 x 1.5) IP66/IP67 2 x (1 NO/2 NC) Slow-action contacts without actuator head

product brand name SIRIUS

product designation Mechanical safety switches

product type designation 3SE5

manufacturer's article number

? of the supplied switching contacts 1x 3SE5000-0BA00, 1x 3SE5060-0BA00

? of the supplied empty enclosure with cover 3SE5162-0AA00

suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 400 V

degree of pollution class 3

surge voltage resistance rated value 6 kV

protection class IP IP66/IP67

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 5 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 5 000 000

Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 6 000

thermal current 10 A

reference code according to IEC 81346-2 B

continuous current of the C characteristic MCB 1 A; for a short-circuit current smaller than 400 A

continuous current of the quick DIAZED fuse link 10 A; for a short-circuit current smaller than 400 A

continuous current of the DIAZED fuse link gG 6 A

active p...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5162-0BA00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.