

INDUSTRIAL COMPONENT DATA

3SE5162-0CH01 SIEMENS Position switch 3SE5162 Metal enclosure XL, 56 mm wide with twist lever 27 mm, made of..

Brand: SIEMENS | Manufacturer Part Number: 3SE5162-0CH01



Manufacturer	SIEMENS
MPN / Reference	3SE5162-0CH01
Catalog number	51620
Category	End switch
Minimum order	1 Pcs
Document ID	EO-762F460375
Generated	2026-08-06

Product Overview

Position switch 3SE5162 Metal enclosure XL, 56 mm wide with twist lever 27 mm, made of metal/plastic roller 19 mm

Device connection 3 x (M20 x 1.5) 2 x (1 NO/1 NC) Quick action contacts IP66/IP67

SIRIUS POSITION SWITCH 3SE5162, METAL ENCLOSURE XL,56MM WIDE WITH TWIST LEVER 27MM, FROM METAL AND PLASTIC ROLLER 19MM DEVICE CONNECTION 3X(M20X1.5), 2X (1NO/1NC) SNAP-ACTION CONTACTS; IP66/ IP67.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

Position switch 3SE5162 Metal enclosure XL, 56 mm wide with twist lever 27 mm, made of metal/plastic roller 19 mm

Device connection 3 x (M20 x 1.5) 2 x (1 NO/1 NC) Quick action contacts IP66/IP67

product brand name SIRIUS

product designation Mechanical position switches

product type designation 3SE5

manufacturer's article number

? of the supplied basic switch 3SE5162-OCA00

? of the supplied actuator head for position switches 3SE5000-0AH00

? of the supplied operating lever 3SE5000-0AA01

? of the supplied switching contacts 1x 3SE5000-0CA00, 1x 3SE5060-0CA00

? of the supplied empty enclosure with cover 3SE5162-0AA00

suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 400 V

degree of pollution class 3

surge voltage resistance rated value 6 kV

protection class IP IP66/IP67

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 5 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 5 000 000

Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 6 000

thermal current 10 A

material of the enclosure of the switch head plastic

reference code according to IEC 81346-2 B

continuous current o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5162-0CH01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.