

INDUSTRIAL COMPONENT DATA

3SE5162-0CH12-1AN5 SIEMENS SIRIUS position switch Metal enclosure XL, 56 mm wide, with twist lever 27 mm mad..

Brand: SIEMENS | Manufacturer Part Number: 3SE5162-0CH12-1AN5



Manufacturer	SIEMENS
MPN / Reference	3SE5162-0CH12-1AN5
Catalog number	51620
Category	End switch
Minimum order	1 Pcs
Document ID	EO-A1FFB61F30
Generated	2026-08-06

Product Overview

SIRIUS position switch Metal enclosure XL, 56 mm wide, with twist lever 27 mm made from Stainless steel, Stainless steel roller 19 mm, Device connection 3x(M20x1.5), Increased corrosion protection (increased corrosion protection) gold-plated contacts, 2x(1 NO/1 NC) Quick action contacts, IP66/IP67; suitable for use at -40 degrees

SIRIUS position switch metal enclosure XL, 56mm wide, with twist lever 27mm made of h.g. st., h.g. st. roller 19mm, device connection 3x(M20x1.5), increased corrosion protection, hard gold-plated contacts: 2x(1NO/1NC) snap act. contacts, IP66/IP67; suitable for use at -40 deg.. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays
--------------	---

Additional Product Information

Technical data

SIRIUS position switch Metal enclosure XL, 56 mm wide, with twist lever 27 mm made from Stainless steel, Stainless steel roller 19 mm, Device connection 3x(M20x1.5), Increased corrosion protection (increased corrosion protection) gold-plated contacts, 2x(1 NO/1 NC) Quick action contacts, IP66/IP67; suitable for use at -40 degrees

product brand name SIRIUS

product designation Mechanical position switches

product type designation 3SE5

manufacturer's article number

? of the supplied actuator head for position switches 3SE5000-0AH00

? of the supplied operating lever 3SE5000-0AA12

? of the supplied switching contacts 1x 3SE5000-0CA00-1AC1, 1x 3SE5060-0CA00-1AC1 on request

? of the supplied empty enclosure with cover 3SE5162-0AA00-1CA0, on request

suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 400 V

degree of pollution class 3

surge voltage resistance rated value 6 kV

protection class IP IP66/IP67

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 5 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 5 000 000

Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 6 000 thermal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5162-0CH12-1AN5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.