

INDUSTRIAL COMPONENT DATA

3SE5162-0CH63-1AN4 SIEMENS SIRIUS position switch Metal enclosure XL, 56 mm wide, with twist lever, adjustab..

Brand: SIEMENS | Manufacturer Part Number: 3SE5162-0CH63-1AN4



Manufacturer	SIEMENS
MPN / Reference	3SE5162-0CH63-1AN4
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-A9ECA28AC9
Generated	2026-08-06

Product Overview

SIRIUS position switch Metal enclosure XL, 56 mm wide, with twist lever, adjustable length with grid hole, stainless steel lever, stainless steel roller 19 mm, Increased corrosion protection (ICP), connection 3xM20x1.5, gold-plated contacts: 2x(1 NO/1 NC) snap-action contacts, adapter 3SX5100-3B (with toothed lock washer) enclosed

SIRIUS position switch XL metal box 56 mm wide, with articulated lever, adjustable length with reticle drills, stainless steel lever, 19 mm stainless steel roller, enhanced corrosion protection (EKS), connection 3 × M20 × 1.5, gold contacts: 2x(1 NA/1 NC) sudden action contacts, Adapter 3SX5100-3B (with toothed washer) attached. Manufactured to order.

Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

Additional Product Information

Technical data

SIRIUS position switch Metal enclosure XL, 56 mm wide, with twist lever, adjustable length with grid hole, stainless steel lever, stainless steel roller 19 mm, Increased corrosion protection (ICP), connection 3xM20x1.5, gold-plated contacts: 2x(1 NO/1 NC) snap-action contacts, adapter 3SX5100-3B (with toothed lock washer) enclosed

product brand name SIRIUS

product designation Mechanical position switches

product type designation 3SE5

manufacturer's article number

? of the supplied actuator head for position switches 3SE5000-0AH00

? of the supplied operating lever 3SE5000-0AA63

? of the supplied switching contacts 1x 3SE5000-0CA00-1AC1, 1x 3SE5060-0CA00-1AC1 on request

? of the supplied empty enclosure with cover 3SE5162-0AA00-1CA0, on request

accessories included Adapter 3SX5100-1A

suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 400 V

degree of pollution class 3

surge voltage resistance rated value 6 kV

protection class IP IP66/IP67

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 5 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 5 000 000

Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5162-0CH63-1AN4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.