

INDUSTRIAL COMPONENT DATA

3SE5212-0KC05-1AJ0 SIEMENS Position switch Metal enclosure according to EN 50047, 31 mm Device connection 1

..

Brand: SIEMENS | Manufacturer Part Number: 3SE5212-0KC05-1AJ0



Manufacturer	SIEMENS
MPN / Reference	3SE5212-0KC05-1AJ0
Catalog number	52120
Category	End switch
Minimum order	1 Pcs
Document ID	EO-C822F8C439
Generated	2026-08-05

Product Overview

Position switch Metal enclosure according to EN 50047, 31 mm Device connection 1 x (M20 x 1.5) 1 NO/2 NC slow-action contacts Rounded plunger, Form B functional at -40 °C Shock and vibration test according to EN 61373, Category 1B SIRIUS POSITION SWITCH; METAL CASE ACCORDING TO EN50047, 31MM CONNECTION DEVICES 1X (M20X1,5); 1NA/2NC CONTACTS NORMAL ACTION, REINFORCED STEM, FORM B, FUNCTIONALITY A -40 GR., SHOCK AND VIBRATION TEST ACCORDING TO EN61373, CATEGORY 1B. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

Additional Product Information

Technical data

Position switch Metal enclosure according to EN 50047, 31 mm Device connection 1 x (M20 x 1.5) 1 NO/2 NC slow-action contacts Rounded plunger, Form B functional at -40 °C Shock and vibration test according to EN 61373, Category 1B

product brand name SIRIUS

product designation Mechanical position switches

product type designation 3SE5

manufacturer's article number

? of the supplied switching contacts 3SE5000-0KA00

suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 400 V

degree of pollution class 3

surge voltage resistance rated value 6 kV

protection class IP IP66/IP67

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

? for railway applications according to EN 61373 Category 1, Class B

vibration resistance

? according to IEC 60068-2-6 0.35 mm/5g

? for railway applications according to EN 61373 Category 1, Class B

mechanical service life (switching cycles) typical 15 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 10 000 000

Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 6 000

thermal current 10 A

material of the enclosure of the switch head metal

reference code according to IEC 81346-2 B

continuous current of the C characteristic MCB 1 A; for a short-circuit current smalle...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5212-0KC05-1AJ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.