

INDUSTRIAL COMPONENT DATA

3SE5232-0GC05 SIEMENS position switch plastic enclosure according to DIN EN 50047, 31 mm device connection 1..

Brand: SIEMENS | Manufacturer Part Number: 3SE5232-0GC05



Manufacturer	SIEMENS
MPN / Reference	3SE5232-0GC05
Catalog number	52320
Category	End switch
Minimum order	1 Pcs
Document ID	EO-04E963A8AC
Generated	2026-08-06

Product Overview

position switch plastic enclosure according to DIN EN 50047, 31 mm device connection 1 x (M20 x 1.5) 1 NO/1 NC
quick-action contacts 2 x 2 mm contact gap rounded plunger form B
SIRIUS Int. position, plastic case 31mm, connection 1x(M20X1,5), contacts sudden action 1NA/1NC, reinforced stem.
Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

position switch plastic enclosure according to DIN EN 50047, 31 mm device connection 1 x (M20 x 1.5) 1 NO/1 NC
quick-action contacts 2 x 2 mm contact gap rounded plunger form B
product brand name SIRIUS
product designation Mechanical position switches
product type designation 3SE5
manufacturer's article number
? of the supplied switching contacts 3SE5000-0GA00
? of the supplied empty enclosure with cover 3SE5232-0AC05
suitability for use safety switch Yes
General technical data
product function positive opening Yes

insulation voltage rated value 400 V

degree of pollution class 3

surge voltage resistance rated value 6 kV

protection class IP IP65

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance

? according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 15 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 10 000 000

Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 6 000

thermal current 10 A

material of the enclosure of the switch head plastic

reference code according to IEC 81346-2 B

continuous current of the C characteristic MCB 1 A; for a short-circuit current smaller than 400 A

continuous current of the quick DIAZED fuse link 10 A; for a short-circuit current smaller than 400 A

continuous current of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5232-0GC05 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.