


INDUSTRIAL COMPONENT DATA

3SE5232-0HK25 SIEMENS Position switch Plastic enclosure according to EN 50047, 31 mm Device connection 1 x (..

Brand: SIEMENS | Manufacturer Part Number: 3SE5232-0HK25



Manufacturer	SIEMENS
MPN / Reference	3SE5232-0HK25
Catalog number	52320
Category	End switch
Minimum order	1 Pcs
Document ID	EO-8A26CD031E
Generated	2026-08-06

Product Overview

Position switch Plastic enclosure according to EN 50047, 31 mm Device connection 1 x (M20 x 1.5) 1 NO/1 NC quick action contacts integrated (not replaceable) Twist lever, 21 mm long right/left adjustable with plastic roller 30 mm SIRIUS Int. position, 31mm plastic box, 1x connection(M20X1,5), integrated 1NA/1NC sudden action contacts, long roller lever. Ajust., with plastic roller 30mm. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays
--------------	---

Additional Product Information

Technical data

Position switch Plastic enclosure according to EN 50047, 31 mm Device connection 1 x (M20 x 1.5) 1 NO/1 NC quick action contacts integrated (not replaceable) Twist lever, 21 mm long right/left adjustable with plastic roller 30 mm

product brand name SIRIUS

product designation Mechanical position switches

product type designation 3SE5

manufacturer's article number

? of the supplied actuator head for position switches 3SE5000-0AK00

? of the supplied operating lever 3SE5000-0AA25

suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 400 V
degree of pollution class 3
surge voltage resistance rated value 6 kV
protection class IP IP65
shock resistance
? according to IEC 60068-2-27 30g / 11 ms
vibration resistance
? according to IEC 60068-2-6 0.35 mm/5g
mechanical service life (switching cycles) typical 15 000 000
electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000
electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 10 000 000
Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 6 000
thermal current 10 A
material of the enclosure of the switch head plastic
reference code according to IEC 81346-2 B
continuous current of the C characteristic MCB 1 A; for a short-circuit current smaller than 400 A
continuous current of the quick DIAZED fuse link 10 A; for a sho...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5232-0HK25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.