

INDUSTRIAL COMPONENT DATA

3SE6315-1BB03 SIEMENS Contact-free safety switches RFID Rectangular 106 mm x 25 mm Individually coded, singl..

Brand: SIEMENS | Manufacturer Part Number: 3SE6315-1BB03



Manufacturer	SIEMENS
MPN / Reference	3SE6315-1BB03
Catalog number	63151
Category	Magnetic proximity switch
Minimum order	1 Pcs
Document ID	EO-2F0554DF77
Generated	2026-08-02

Product Overview

Contact-free safety switches RFID Rectangular 106 mm x 25 mm Individually coded, single teach-in, with M12 connector 8-pole and magnet latching 18 N. Order actuator separately: 3SE6310-1BC01

RECTANGULAR NON-CONTACT RFID SAFETY SWITCH 25MM X 91MM, INDIVIDUALLY COFIFIED, FOR SINGLE TEACH-IN WITH 8-POLE M12 CONNECTOR AND MAGNETIC RETENTION, SEPARATELY ORDER ACTUATOR 3SE6310-1BC01

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

Additional Product Information

Technical data

Contact-free safety switches RFID Rectangular 106 mm x 25 mm Individually coded, single teach-in, with M12 connector 8-pole and magnet latching 18 N. Order actuator separately: 3SE6310-1BC01

product brand name SIRIUS

product designation RFID safety switch

design of the product Rectangular sensor unit

product type designation 3SE63

suitability for use safety-related circuits Yes

General technical data

product function

? positive opening No

? cross-circuit/short-circuit recognition Yes
product feature individually coded, learnable once, with magnet latching
type of voltage of the operating voltage DC
protection class IP IP65, IP67, IP69k
shock resistance according to IEC 60068-2-27 Sinusoidal half-wave 30g / 11 ms
vibration resistance according to IEC 60068-2-6 10 ... 55 Hz: 1 mm
Substance Prohibitance (Date) 07/01/2006
type of voltage DC
height of the sensor 22 mm
length of the sensor 106 mm
width of the sensor 25 mm
material of the active sensor area plastic
mechanical installation condition for sensor flush installation possible
operating voltage rated value 24 V
operational current rated value 600 mA
design of the interface for safety-related communication connector M12
transmission frequency rated value 125 kHz
Enclosure
material of the enclosure plastic
material of cable sheath PVC
Actuator
design of the actuating element RFID
Contact
switching frequency 1 Hz
operating distance 12 mm
assured operating distance OFF 16 mm
assured operating distance ON 10 mm....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE6315-1BB03 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.