

INDUSTRIAL COMPONENT DATA

3SE6604-2BA01 SIEMENS Magnet switch Contact block 25 x 88 mm 2 NC with M8 connector, 4-pole

Brand: SIEMENS | Manufacturer Part Number: 3SE6604-2BA01



Manufacturer	SIEMENS
MPN / Reference	3SE6604-2BA01
Catalog number	66042
Category	Magnetic proximity switch
Minimum order	1 Pcs
Document ID	EO-7451977A80
Generated	2026-08-04

Product Overview

magnetically-operated switch, contact block, rectangular, large: 25x 88 mm, 2 NC, with M8 plug 4-pole, required solenoid 3SE6704-2BA or with increased switching separation 3SE6701-2BA. accessories: coupling with connecting cable 5 m 3SX5601-3GA05

MAGNETIC SWITCH BLOCK DESIRIUS ContactorsS 25XX88MM, 2NC, WITH M8 CONNECTOR 4 poles,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

magnetically-operated switch, contact block, rectangular, large: 25x 88 mm, 2 NC, with M8 plug 4-pole, required solenoid 3SE6704-2BA or with increased switching separation 3SE6701-2BA. accessories: coupling with connecting cable 5 m 3SX5601-3GA05

product brand name SIRIUS

product designation Magnetically operated switch

design of the product Rectangular sensor unit

product type designation 3SE66

suitability for use safety-related circuits Yes

General technical data

product function

? positive opening No

? cross-circuit/short-circuit recognition No
type of voltage of the operating voltage AC/DC
protection class IP IP67
shock resistance according to IEC 60068-2-27 Sinusoidal half-wave 30g / 11 ms
vibration resistance according to IEC 60068-2-6 10 ... 55 Hz: 1 mm
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 07/01/2006
type of voltage AC/DC
height of the sensor 13 mm
length of the sensor 88 mm
width of the sensor 25 mm
material of the active sensor area plastic
mechanical installation condition for sensor no flush installation possible
operating voltage rated value 60 V
operational current rated value 400 mA
operating power rated value 10 W
number of NC contacts for auxiliary contacts 2
number of NO contacts for auxiliary contacts 0
Enclosure
design of the housing block
material of the enclosure plastic
Actuator
design of the actuating element magnet
Contact
circuit principle reed switches
switching frequency 5 Hz
assured operating dista...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE6604-2BA01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.