

INDUSTRIAL COMPONENT DATA

3SE6614-4CA01 SIEMENS Magnet switch Contact block 25 x 88 mm, for door hinge on the left Contact elements: S..

Brand: SIEMENS | Manufacturer Part Number: 3SE6614-4CA01



Manufacturer	SIEMENS
MPN / Reference	3SE6614-4CA01
Catalog number	66144
Category	Magnetic proximity switch
Minimum order	1 Pcs
Document ID	EO-490803B995
Generated	2026-08-06

Product Overview

Magnet switch Contact block 25 x 88 mm, for door hinge on the left Contact elements: Safety contacts 2 NC with M8 connector, 4-pole with combi connection Screw/latching connection with LED, the matching solenoid 3SE6714-2CA or offset by 90° 3SE6724-2CA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

Magnet switch Contact block 25 x 88 mm, for door hinge on the left Contact elements: Safety contacts 2 NC with M8 connector, 4-pole with combi connection Screw/latching connection with LED, the matching solenoid 3SE6714-2CA or offset by 90° 3SE6724-2CA

product brand name SIRIUS

product designation Magnetically operated switch

design of the product Rectangular sensor unit

product type designation 3SE66

suitability for use safety-related circuits Yes

General technical data

product function

? positive opening No

? control function for downstream devices No

? cross-circuit/short-circuit recognition Yes
type of voltage of the operating voltage DC
protection class IP IP67
shock resistance according to IEC 60068-2-27 Sinusoidal half-wave 30g / 11 ms
vibration resistance according to IEC 60068-2-6 10 ... 55 Hz: 1 mm
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 07/01/2006
type of voltage DC
height of the sensor 25 mm
length of the sensor 13 mm
width of the sensor 88 mm
material of the active sensor area Plastic, glass-fiber reinforced thermoplastic
mechanical installation condition for sensor can be installed almost flush
operating voltage rated value 24 V
operational current rated value 10 mA
operating power rated value 0.24 W
number of NC contacts for auxiliary contacts 2
number of NC contacts safety-related 2
number of NO contacts for auxiliary contacts 0
number of NO contacts safety-related 0
Enclosure
material of the enclosure Plastic, g...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE6614-4CA01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.