

INDUSTRIAL COMPONENT DATA

3SE7120-2DD01 SIEMENS Cable-operated switch Metal enclosure, 2x M20 x1.5 1 NO+1 NC, without latching for wir..

Brand: SIEMENS | Manufacturer Part Number: 3SE7120-2DD01



Manufacturer	SIEMENS
MPN / Reference	3SE7120-2DD01
Catalog number	71202
Category	Emergency stop pull cord switch
Minimum order	1 Pcs
Document ID	EO-40FA7F4578
Generated	2026-08-06

Product Overview

cable-operated switch metal enclosure, 2x M20 x1.5; 1 NO+1 NC, without latching, for cable lengths up to 5 m, only Bowden cable function, 55 N spring, maximum actuating force 80 N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

cable-operated switch metal enclosure, 2x M20 x1.5; 1 NO+1 NC, without latching, for cable lengths up to 5 m, only Bowden cable function, 55 N spring, maximum actuating force 80 N

product brand name SIRIUS

product designation cable-operated switch

product type designation 3SE7

General technical data

product function EMERGENCY STOP function No

product component light source No

insulation voltage rated value 400 V

degree of pollution class 3

surge voltage resistance rated value 6 kV

protection class IP IP65

mechanical service life (switching cycles) typical 1 000 000

thermal current 6 A
reference code according to IEC 81346-2 S
continuous current of the DIAZED fuse link gG 6 A
Substance Prohibitance (Date) 07/01/2006
number of NC contacts for auxiliary contacts 1
number of NO contacts for auxiliary contacts 1
operational current at AC-15
? at 240 V rated value 6 A
? at 400 V rated value 6 A
operational current at DC-13
? at 24 V rated value 3 A
? at 250 V rated value 0.27 A
Enclosure
material of the enclosure metal
material of the enclosure cover Plastic
product component EMERGENCY STOP device No
color
? of the enclosure black
? of the enclosure top part grey
coating of the enclosure painted
circuit principle Jump function
material of the contact Silver
number of switching contacts safety-related 1
Connections/ Terminals
type of electrical connection screw-type terminals
type of connectable conductor cross-sections
? solid 2x (0.5 ... 2.5 mm²)
? finely stranded....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE7120-2DD01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.