

INDUSTRIAL COMPONENT DATA

3SF1324-1SF21-1BK4 SIEMENS Safety position switch with tumbler Locking force 1300 N 5 directions of approach..

Brand: SIEMENS | Manufacturer Part Number: 3SF1324-1SF21-1BK4



Manufacturer	SIEMENS
MPN / Reference	3SF1324-1SF21-1BK4
Catalog number	13241
Category	Position switch with guard locking
Minimum order	1 Pcs
Document ID	EO-885AA2D64C
Generated	2026-08-06

Product Overview

safety position switch with tumbler, locking force 1300 N, 5 directions of approaches, plastic enclosure, M12 plug, ASIsafe integrated, high degree of protection IP69, IEC 60529, channel 1=actuator 2 NC according to principle of 2v2 evaluation channel 2=magnet 1 NC, spring-locked, escape release on front, magnet voltage 24 V AC/DC; no additional 24 V supply required. monitoring actuator 2 NC/1 NO monitoring magnet 2 NC/1 NO the matching separate actuator 3SE5000-0AV0./-0AW5. must be ordered separately.

INT. POS. SAFETY C.RETENTION PROTECTION IP69,IEC 60529 FORCE RETENC.1300N, 5 SENSES OF ATTACK PLASTIC BOX, CONNECTOR M12 ASI-SAFE INTEGRATED CAN1 = ACTUATOR 2NC EVALUATION PRINCIPLE 2DE2 CAN2=ELECTROMAGNET 1NC SPRING-INTERLOCKED, UNLOCK. LEAKAGE IN FRONT VOLTAGE ELECTROMAGNET 24V DC/AC, MONITORING ACTUATOR 2NC/1N SURVEILLANCE ELECTROMAGNET 2NC/1NA, THE ACTUATOR SEPARATED CORRESP. 3SE5000-0AV0. SEPARATELY REQUESTED. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE

Additional Product Information

Product

Article Number (Market Facing Number) 3SF1324-1SF21-1BK4

Product Description safety position switch with tumbler, locking force 1300 N, 5 directions of approaches, plastic enclosure, M12 plug, ASIsafe integrated, high degree of protection IP69, IEC 60529, channel 1=actuator 2 NC according to principle of 2v2 evaluation channel 2=magnet 1 NC, spring-locked, escape release on front, magnet voltage 24 V AC/DC; no additional

24 V supply required. monitoring actuator 2 NC/1 NO monitoring magnet 2 NC/1 NO the matching separate actuator 3SE5000-0AV0./-0AW5. must be ordered separately.

Product family 3SF1, plastic enclosures with locking force greater than 1 000 N

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 42A / 42A

Surcharge for Raw Materials None

Metal Factor None

Delivery information

Export Control Regulations AL : N / ECCN : N

Standard lead time ex-works 5 Day/Days

Net Weight (kg) 0,860 Kg

Packaging Dimension 151,00 x 251,50 x 68,50

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Product Information

EAN 4011209944817

UPC 804766133275

Commodity Code 85365080

LKZ_FDB/ CatalogID CC-IC10

Product Group 3758

Group Code R711

Country of origin Germany

Compliance with the substance restrictions according to RoHS directive Since: 01.03.2017

Product class A: Standard product which is a stock item could be returned within the returns guidelines/period.

WEEE (2012/19/EU) Take-Back....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SF1324-1SF21-1BK4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.