

INDUSTRIAL COMPONENT DATA

3SF1324-1SG21-1BA4 SIEMENS Safety position switch with tumbler Locking force 1300 N 5 directions of approach..

Brand: SIEMENS | Manufacturer Part Number: 3SF1324-1SG21-1BA4



Manufacturer	SIEMENS
MPN / Reference	3SF1324-1SG21-1BA4
Catalog number	13241
Category	Position switch with guard locking
Minimum order	1 Pcs
Document ID	EO-CC8A2B9EC8
Generated	2026-08-05

Product Overview

Safety position switch with tumbler Locking force 1300 N 5 directions of approaches Plastic enclosure, M12 connector ASIsafe integrated Channel 1=actuator 2 NC According to principle of 2v2 evaluation Channel 2=magnet 1 NC spring-locked Escape release at the rear and Auxiliary release on front Magnet voltage 24 V AC/DC Monitoring actuator 2 NC/1 NO Monitoring magnet 2 NC/1 NO The matching separate Actuator 3SE5000-0AV0 must be ordered separately POS. SECURITY WITH RETENTION RETENTION FORCE RETENC. 1300N,5 DIRECTION ATAQ. PLASTIC BOX, M12 CONNECTOR, ASI-SAFE INTEGRATED, CAN1= 2NC ACTUATOR, ACCORDING TO EVALUATION 2V2, CAN2= ELECTROMAGNET 1ST SPRING INTERLOCKING, UNLOCKING. FRAME IN FRONT AND UNWRAP. AUXILIARY IN FRONT VOLTAGE ELECTROMAGNET 24V DC/AC, SURVEILLANCE ACTUATOR 2OE/1S, SURVEILLANCE IMAN 2NC/1NA, THE CORRESPONDING SEPARATE ACTUATOR 3SE5000-0AV0. SEPARATE REQUEST. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE

Additional Product Information

Technical data

Safety position switch with tumbler Locking force 1300 N 5 directions of approaches Plastic enclosure, M12 connector ASIsafe integrated Channel 1=actuator 2 NC According to principle of 2v2 evaluation Channel 2=magnet 1 NC spring-locked Escape release at the rear and Auxiliary release on front Magnet voltage 24 V AC/DC Monitoring actuator 2 NC/1 NO Monitoring magnet 2 NC/1 NO The matching separate Actuator 3SE5000-0AV0 must be ordered separately product brand name SIRIUS

product designation Mechanical safety switches

design of the product with separate actuator and with tumbler

product type designation 3SF13

manufacturer's article number of the optional actuators 3SE5000-0AV01 standard actuator, 3SE5000-0AV02 actuator with vertical mounting, 3SE5000-0AV03 actuator with transverse mounting, 3SE5000-0AV04 radius actuator left, 3SE5000-0AV05 universal actuator, 3SE5000-0AV06 radius actuator right, 3SE5000-0AV07 heavy duty actuator

suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 30 V

degree of pollution class 3

surge voltage resistance rated value 0.8 kV

protection class IP IP65/IP67

shock resistance 30g / 11 ms

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance 0.35 mm / 5g

? according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 1 000 000

material of the enclosure of the switch head plastic

reference code according to IEC 81346-2 B

lock...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SF1324-1SG21-1BA4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.