

INDUSTRIAL COMPONENT DATA

3SU1000-0AB70-0AA0 SIEMENS Pushbutton, 22 mm, round, plastic, clear, pushbutton, flat momentary contact type

Brand: SIEMENS | Manufacturer Part Number: 3SU1000-0AB70-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1000-0AB70-0AA0
Catalog number	10000
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-38E319A795
Generated	2026-08-04

Product Overview

Pushbutton, 22 mm, round, plastic, clear, pushbutton, flat momentary contact type
PUSH BUTTON, 22MM, ROUND, PLASTIC, TRANSPARENT, BUTTON, MOMENTARY FLUSH.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data
Pushbutton, 22 mm, round, plastic, clear, pushbutton, flat momentary contact type
product brand name SIRIUS ACT
product designation Pushbuttons
design of the product Actuating/signaling element
product type designation 3SU1
product line Plastic, black, 22 mm
Enclosure
number of command points 1
Actuator
design of the actuating element Flat button
principle of operation of the actuating element momentary contact type
product extension optional
? light source No

? contact module Yes
color of the actuating element clear
material of the actuating element plastic
shape of the actuating element round
outer diameter of the actuating element 29.5 mm
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black
General technical data
protection class IP IP66, IP67, IP69(IP69K)
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
? for railway applications according to EN 61373 Category 1, Class B
operating frequency maximum 3 600 1/h
mechanical service life (switching cycles) typical 10 000 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 10/01/2014
Ambient conditions
ambient temperature
? during operation -25 ... +70 °C
? during storage -40

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1000-0AB70-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.