

**INDUSTRIAL COMPONENT DATA**

# 3SU1000-0CB10-0AA0 SIEMENS Pushbutton, 22 mm, round, plastic, black, Front ring, raised momentary contact ty..

Brand: SIEMENS | Manufacturer Part Number: 3SU1000-0CB10-0AA0



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 3SU1000-0CB10-0AA0            |
| Catalog number  | 10000                         |
| Category        | Front element for push button |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-E0C2A98014                 |
| Generated       | 2026-08-03                    |

## Product Overview

Pushbutton, 22 mm, round, plastic, black, Front ring, raised momentary contact type  
PUSHBUTTON, 22MM, ROUND, PLASTIC, BLACK, FRONT RING, PROTRUDING, MOMENTARY

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

## Additional Product Information

Technical data  
Pushbutton, 22 mm, round, plastic, black, Front ring, raised momentary contact type  
product brand name SIRIUS ACT  
product designation Pushbuttons  
design of the product Actuating/signaling element  
product type designation 3SU1  
product line Plastic, black, 22 mm  
Enclosure  
number of command points 1  
Actuator  
design of the actuating element Flat button  
principle of operation of the actuating element momentary contact type  
product extension optional  
? light source No

? contact module Yes  
color of the actuating element black  
material of the actuating element plastic  
shape of the actuating element round  
outer diameter of the actuating element 29.5 mm  
Front ring  
product component front ring Yes  
design of the front ring high  
material of the front ring plastic  
color of the front ring black  
General technical data  
protection class IP IP66, IP67, IP69(IP69K)  
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13  
shock resistance  
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms  
? for railway applications according to EN 61373 Category 1, Class B  
vibration resistance  
? according to IEC 60068-2-6 10 ... 500 Hz: 5g  
? for railway applications according to EN 61373 Category 1, Class B  
operating frequency maximum 3 600 1/h  
mechanical service life (switching cycles) typical 10 000 000  
reference code according to IEC 81346-2 S  
Substance Prohibitance (Date) 10/01/2014  
Ambient conditions  
ambient temperature  
? during operation -25 ... +70 °C  
? during storage -40 .....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1000-0CB10-0AA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.