

INDUSTRIAL COMPONENT DATA

3SU1000-4BL01-0AA0 SIEMENS RONIS key-operated switch, 22 mm, round, plastic, lock number SB30, with 2 keys, ..

Brand: SIEMENS | Manufacturer Part Number: 3SU1000-4BL01-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1000-4BL01-0AA0
Catalog number	10004
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-ABB2B48069
Generated	2026-08-04

Product Overview

RONIS key-operated switch, 22 mm, round, plastic, lock number SB30, with 2 keys, 3 switch positions I-O-II, latching, actuating angle 2x45°, 10:30h/12h/13:30h, key removal O, possible special locks: SB31, 421, 455

RONIS KEY SWITCH, 22MM, ROUND, PLASTIC, NO. SB30 LOCK, WITH 2 KEYS, 3 POSITIONS I-O-II, SUSTAINED, ANGLE 2X45 DEGREES, 10:30H/12H/13:30H, EXTRACTION POSITION OR, POSSIBLE SPECIAL LOCKS: SB31, 421, 455

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

Additional Product Information

Technical data

RONIS key-operated switch, 22 mm, round, plastic, lock number SB30, with 2 keys, 3 switch positions I-O-II, latching, actuating angle 2x45°, 10:30h/12h/13:30h, key removal O, possible special locks: SB31, 421, 455

product brand name SIRIUS ACT

product designation Key-operated switches

design of the product Actuating/signaling element

product type designation 3SU1

product line Plastic, black, 22 mm

manufacturer's article number of included key 3SU1950-0FB80-0AA0

Actuator

principle of operation of the actuating element latching, 2x45° (10:30 h/12 h/13:30 h)

product extension optional light source No
color
? of the actuating element silver
material of the actuating element metal
shape of the actuating element Key
outer diameter of the actuating element 29.5 mm
number of switching positions 3
switch position for key distraction O
actuating angle
? clockwise 45°
? anticlockwise 45°
lock make RONIS
key number SB30
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black
General technical data
protection class IP IP66, IP67, IP69(IP69K)
? of the terminal IP20
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
? for railway applications according to EN 61373 Cat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1000-4BL01-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.