

INDUSTRIAL COMPONENT DATA

3SU1000-5BF01-0AA0 SIEMENS key-operated switch Siemens, 22 mm, round, plastic, lock number SSG10, with 2 key..

Brand: SIEMENS | Manufacturer Part Number: 3SU1000-5BF01-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1000-5BF01-0AA0
Catalog number	10005
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-9021FC3EBD
Generated	2026-08-04

Product Overview

key-operated switch Siemens, 22 mm, round, plastic, lock number SSG10, with 2 keys, 2 switch positions O-I, latching, actuating angle 90°, 10:30h/13:30h, key removal O
CES KEY SWITCH, 22MM, ROUND, PLASTIC, LOCK NO. SSG10, WITH 2 WRENCHES, 2 POSITIONS O-I, HELD, 90 DEGREE ANGLE, 10:30H/13:30H, EXTRACTION POSITION O.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

Additional Product Information

Technical data

key-operated switch Siemens, 22 mm, round, plastic, lock number SSG10, with 2 keys, 2 switch positions O-I, latching, actuating angle 90°, 10:30h/13:30h, key removal O
product brand name SIRIUS ACT
product designation Key-operated switches
design of the product Actuating/signaling element
product type designation 3SU1
product line Plastic, black, 22 mm
manufacturer's article number of included key 3SU1950-0FP80-0AA0
Actuator

principle of operation of the actuating element latching, 90° (10:30 h/13:30 h)

product extension optional light source No

color

? of the actuating element silver

material of the actuating element metal

shape of the actuating element Key

outer diameter of the actuating element 29.5 mm

number of switching positions 2

switch position for key distraction O

actuating angle

? clockwise 90°

lock make Siemens

key number SSG10

Front ring

product component front ring Yes

design of the front ring Standard

material of the front ring plastic

color of the front ring black

General technical data

protection class IP IP66, IP67, IP69(IP69K)

? of the terminal IP20

degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

shock resistance

? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms

? for railway applications according to EN 61373 Category 1, Class B

vibration resistance

? according to IEC 60068-2-6 10 ... 500 Hz: 5g

? for railway applications according to EN 61373 Category 1, Class B

operating frequency maximum 1 800 1/h

mechanical serv...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1000-5BF01-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.