


INDUSTRIAL COMPONENT DATA

3SU1000-7AF10-0AA0 SIEMENS Coordinate switch, 22 mm, round, plastic, black, 4 switch positions, momentary co..

Brand: SIEMENS | Manufacturer Part Number: 3SU1000-7AF10-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1000-7AF10-0AA0
Catalog number	10007
Category	Control switch, Joystick
Minimum order	1 Pcs
Document ID	EO-06A3723403
Generated	2026-08-04

Product Overview

Coordinate switch, 22 mm, round, plastic, black, 4 switch positions, momentary contact type, without mechanical interlocking

MANIPULATOR, 22MM, ROUND, PLASTIC, BLACK, 4 POSITIONS O-I-II-III, MOMENTARY, WITHOUT MECHANICAL INTERLOCKING.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

Technical data

Coordinate switch, 22 mm, round, plastic, black, 4 switch positions, momentary contact type, without mechanical interlocking

product brand name SIRIUS ACT

product designation Coordinate switches

design of the product Actuating/signaling element

product type designation 3SU1

product line Plastic, black, 22 mm

Enclosure

number of command points 1

Actuator

design of the actuating element without mechanical interlock

principle of operation of the actuating element momentary contact type

direction of actuation horizontal / vertical

product extension optional

? light source No

? contact module Yes

color of the actuating element black

material of the actuating element plastic

shape of the actuating element Extended handle

outer diameter of the actuating element 30.5 mm

number of switching positions 4

Maximum deflection angle [°] 30°

Front ring

product component front ring Yes

design of the front ring high

material of the front ring plastic

color of the front ring black

General technical data

protection class IP IP65, IP67

degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

shock resistance

? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms

vibration resistance

? according to IEC 60068-2-6 10 ... 500 Hz: 5g

operating frequency maximum 2 400 1/h

mechanical service life (switching cycles)

? as operating period per direction of actuation typical 500 000

reference code according to IEC 81346-2 S

Substance Prohibitance (Date) 10/01/2014

Safety related d...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1000-7AF10-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.