

INDUSTRIAL COMPONENT DATA

3SU1001-1AD40-0AA0 SIEMENS Illuminated mushroom pushbutton, 22 mm, round, plastic, green, 30 mm, momentary C..

Brand: SIEMENS | Manufacturer Part Number: 3SU1001-1AD40-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1001-1AD40-0AA0
Catalog number	10011
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-79EA0731AC
Generated	2026-08-06

Product Overview

Illuminated mushroom pushbutton, 22 mm, round, plastic, green, 30 mm, momentary contact type
ILLUMINATED MUSHROOM PUSH BUTTON, 22MM, ROUND, PLASTIC, GREEN, 30MM, MOMENTARY.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

Additional Product Information

Technical data

Illuminated mushroom pushbutton, 22 mm, round, plastic, green, 30 mm, momentary contact type

product brand name SIRIUS ACT

product designation Mushroom pushbuttons

design of the product Actuating/signaling element

product type designation 3SU1

product line Plastic, black, 22 mm

Enclosure

number of command points 1

Actuator

design of the actuating element illuminated

principle of operation of the actuating element momentary contact type

product extension optional light source Yes
color of the actuating element green
material of the actuating element plastic
shape of the actuating element round
outer diameter of the actuating element 30 mm
number of switching positions 2
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black
General technical data
product function
? EMERGENCY OFF function No
? EMERGENCY STOP function No
protection class IP IP66, IP67, IP69(IP69K)
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
? for railway applications according to EN 61373 Category 1, Class B
operating frequency maximum 3 600 1/h
mechanical service life (switching cycles) typical 3 000 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 10/01...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1001-1AD40-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.