

INDUSTRIAL COMPONENT DATA

3SU1001-3AB42-0AN0 SIEMENS Illuminated twin pushbutton, 22 mm, round, plastic, green: arrow pointing up, red..

Brand: SIEMENS | Manufacturer Part Number: 3SU1001-3AB42-0AN0



Manufacturer	SIEMENS
MPN / Reference	3SU1001-3AB42-0AN0
Catalog number	10013
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-FD8454CC48
Generated	2026-08-06

Product Overview

Illuminated twin pushbutton, 22 mm, round, plastic, green: arrow pointing up, red: arrow pointing down, pushbuttons, flat ILLUMINATED DOUBLE PUSHBUTTON, 22MM, ROUND, PLASTIC, GREEN:UP ARROW, RED:DOWN ARROW, BUTTONS, GRADES,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

Technical data

Illuminated twin pushbutton, 22 mm, round, plastic, green: arrow pointing up, red: arrow pointing down, pushbuttons, flat
 product brand name SIRIUS ACT
 product designation Twin pushbuttons
 design of the product Actuating/signaling element
 product type designation 3SU1
 product line Plastic, black, 22 mm
 Enclosure
 number of command points 1
 Actuator
 design of the actuating element Flat buttons, illuminated
 principle of operation of the actuating element momentary contact type
 product extension optional

? light source Yes
? contact module Yes
color of the actuating element green / red
material of the actuating element plastic
shape of the actuating element oval
marking of the actuating element Arrow to the top, arrow to the bottom
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black
General technical data
protection class IP IP66, IP67, IP69(IP69K)
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
? for railway applications according to EN 61373 Category 1, Class B
operating frequency maximum 3 600 1/h
mechanical service life (switching cycles) typical 2 000 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 10/01/2014
Ambient...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1001-3AB42-0AN0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.