

INDUSTRIAL COMPONENT DATA

3SU1002-2BF60-0AA0 SIEMENS Selector switch, illuminable, 22 mm, round, plastic, white, selector switch, shor..

Brand: SIEMENS | Manufacturer Part Number: 3SU1002-2BF60-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1002-2BF60-0AA0
Catalog number	10022
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-FFAF0968E5
Generated	2026-08-02

Product Overview

Selector switch, illuminable, 22 mm, round, plastic, white, selector switch, short, 2 switch positions O-I, latching, actuating angle 90°, 10:30h/13:30h

SELECTOR, ILLUMINABLE, 22MM, ROUND, PLASTIC, BLACK, WHITE, HANDLE, SHORT, 2 POSITIONS O-I, SUSTAINED, 90 DEGREE ANGLE, 10:30H/13:30H.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Selector switch, illuminable, 22 mm, round, plastic, white, selector switch, short, 2 switch positions O-I, latching, actuating angle 90°, 10:30h/13:30h

product brand name SIRIUS ACT

product designation Selector switches

design of the product Actuating/signaling element

product type designation 3SU1

product line Plastic, black, 22 mm

Enclosure

number of command points 1

Actuator

design of the actuating element Selector, short

principle of operation of the actuating element latching, 90° (10:30 h/13:30 h)

product extension optional

? light source Yes

? contact module Yes

color of the actuating element white

material of the actuating element plastic

shape of the actuating element Handle

outer diameter of the actuating element 32.3 mm

number of switching positions 2

actuating angle

? clockwise 90°

Front ring

product component front ring Yes

design of the front ring standard

material of the front ring plastic

color of the front ring black

General technical data

protection class IP IP66, IP67, IP69(IP69K)

degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

shock resistance

? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms

? for railway applications according to EN 61373 Category 1, Class B

vibration resistance

? according to IEC 60068-2-6 10 ... 500 Hz: 5g

? for railway applications according to EN 61373 Category 1, Class B

operating frequency maximum 1 800 1/h

mechanical service life (switching cycles) typical 1 000 000

reference code accordin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1002-2BF60-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.