

## INDUSTRIAL COMPONENT DATA

**3SU1050-1HU10-0AA0 SIEMENS Mushroom pushbutton, 22 mm, round, metal, shiny, black, 40 mm, with CES lock, loc..**

Brand: SIEMENS | Manufacturer Part Number: 3SU1050-1HU10-0AA0



|                 |                                        |
|-----------------|----------------------------------------|
| Manufacturer    | SIEMENS                                |
| MPN / Reference | 3SU1050-1HU10-0AA0                     |
| Catalog number  | 10501                                  |
| Category        | Front element for mushroom push-button |
| Minimum order   | 1 Pcs                                  |
| Document ID     | EO-BBE08D4ABC                          |
| Generated       | 2026-08-06                             |

**Product Overview**

mushroom pushbutton, 22 mm, round, metal, shiny, black, 40 mm, with lock Siemens, lock no. VL5, positive latching, according to DIN EN ISO 13850, key-operated release

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

**Additional Product Information**

## Technical data

mushroom pushbutton, 22 mm, round, metal, shiny, black, 40 mm, with lock Siemens, lock no. VL5, positive latching, according to DIN EN ISO 13850, key-operated release

product brand name SIRIUS ACT

product designation Mushroom pushbuttons

design of the product Actuating/signaling element

product type designation 3SU1

product line Metal, shiny, 22 mm

Enclosure

number of command points 1

Actuator

design of the actuating element positive latching

principle of operation of the actuating element latching

product extension optional light source No

color of the actuating element black  
material of the actuating element plastic  
shape of the actuating element round  
outer diameter of the actuating element 40 mm  
type of unlocking device Unlocking  
number of switching positions 2  
Front ring  
product component front ring No  
design of the front ring without  
General technical data  
product function  
? EMERGENCY OFF function No  
? EMERGENCY STOP function No  
protection class IP IP66, IP67, IP69(IP69K)  
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13  
shock resistance  
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms  
vibration resistance  
? according to IEC 60068-2-6 10 ... 500 Hz: 5g  
operating frequency maximum 600 1/h  
mechanical service life (switching cycles) typical 300 000  
reference code according to IEC 81346-2 S  
Substance Prohibitance (Date) 10/01/2014  
Safety related data  
B10 value with high demand rate according to SN 31920 100 000  
proportion of dangerous...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1050-1HU10-0AA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.