

INDUSTRIAL COMPONENT DATA

3SU1050-1JB20-0AA0 SIEMENS EMERGENCY STOP mushroom pushbutton, 22 mm, round, metal, shiny, red, 60 mm, posit..

Brand: SIEMENS | Manufacturer Part Number: 3SU1050-1JB20-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1050-1JB20-0AA0
Catalog number	10501
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-6F61A38B65
Generated	2026-08-04

Product Overview

EMERGENCY STOP mushroom pushbutton, 22 mm, round, metal, shiny, red, 60 mm, positive latching, acc. to EN ISO 13850, rotate-to-unlatch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

Additional Product Information

Technical data

EMERGENCY STOP mushroom pushbutton, 22 mm, round, metal, shiny, red, 60 mm, positive latching, acc. to EN ISO 13850, rotate-to-unlatch

product brand name SIRIUS ACT

product designation EMERGENCY STOP mushroom pushbuttons

design of the product Actuating/signaling element

product type designation 3SU1

product line Metal, shiny, 22 mm

Enclosure

number of command points 1

Actuator

design of the actuating element positive latching

principle of operation of the actuating element latching
product extension optional
? light source No
? contact module Yes
color
? of the actuating element red
material of the actuating element plastic
shape of the actuating element round
outer diameter of the actuating element 60 mm
type of unlocking device pull-to-unlatch mechanism
number of switching positions 2
Front ring
product component front ring No
General technical data
product function
? positive opening Yes
? EMERGENCY OFF function Yes
? EMERGENCY STOP function Yes
protection class IP IP66, IP67, IP69(IP69K)
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
operating frequency maximum 600 1/h
mechanical service life (switching cycles) typical 300 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 10/01/2014
Safety related data
B10 value with high demand rate according to SN 31920 100 000
proportio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1050-1JB20-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.