

**INDUSTRIAL COMPONENT DATA**

# 3SU1050-2AS60-0AA0 SIEMENS Selector switch, 22 mm, round, metal, shiny, white, Rotary knob, 4 switch positio..

Brand: SIEMENS | Manufacturer Part Number: 3SU1050-2AS60-0AA0



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | SIEMENS                           |
| MPN / Reference | 3SU1050-2AS60-0AA0                |
| Catalog number  | 10502                             |
| Category        | Front element for selector switch |
| Minimum order   | 1 Pcs                             |
| Document ID     | EO-94DFB17F45                     |
| Generated       | 2026-08-03                        |

## Product Overview

Selector switch, 22 mm, round, metal, shiny, white, Rotary knob, 4 switch positions I-II-III-IV, latching, Actuating angle 4x90°, 3h/6h/9h/12h

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

## Additional Product Information

**Technical data**

Selector switch, 22 mm, round, metal, shiny, white, Rotary knob, 4 switch positions I-II-III-IV, latching, Actuating angle 4x90°, 3h/6h/9h/12h

product brand name SIRIUS ACT

product designation Selector switches

design of the product Actuating/signaling element

product type designation 3SU1

product line Metal, shiny, 22 mm

Enclosure

number of command points 1

Actuator

design of the actuating element Rotary knob

principle of operation of the actuating element Latching, 4x90° (3/6/9/12 o'clock)

product extension optional

? light source No  
? contact module Yes  
color of the actuating element white  
material of the actuating element plastic  
shape of the actuating element Button  
outer diameter of the actuating element 29.5 mm  
number of switching positions 4  
actuating angle  
? clockwise 360°  
? anticlockwise 360°  
Front ring  
product component front ring Yes  
design of the front ring standard  
material of the front ring Metal, high gloss  
color of the front ring silver  
General technical data  
protection class IP IP66, IP67, IP69(IP69K)  
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13  
shock resistance  
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms  
vibration resistance  
? according to IEC 60068-2-6 10 ... 500 Hz: 5g  
operating frequency maximum 1 800 1/h  
mechanical service life (switching cycles) typical 300 000  
reference code according to IEC 81346-2 S  
Substance Prohibitance (Date) 10/01/2014  
Ambient conditions  
ambient temperature  
? during operation -25...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1050-2AS60-0AA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.