

INDUSTRIAL COMPONENT DATA

3SU1050-3AB66-0AM0 SIEMENS Twin pushbutton, 22 mm, round, metal, shiny, white: arrow pointing left, white: A..

Brand: SIEMENS | Manufacturer Part Number: 3SU1050-3AB66-0AM0



Manufacturer	SIEMENS
MPN / Reference	3SU1050-3AB66-0AM0
Catalog number	10503
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-395988F0C6
Generated	2026-08-06

Product Overview

Twin pushbutton, 22 mm, round, metal, shiny, white: arrow pointing left, white: Arrow pointing right, pushbuttons, flat
DOUBLE PUSHBUTTON, 22MM, ROUND, METAL, BRIGHT, WHITE: LEFT ARROW, WHITE: RIGHT ARROW,
BUTTONS, GRADES,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Twin pushbutton, 22 mm, round, metal, shiny, white: arrow pointing left, white: Arrow pointing right, pushbuttons, flat

product brand name SIRIUS ACT

product designation Twin pushbuttons

design of the product Actuating/signaling element

product type designation 3SU1

product line Metal, shiny, 22 mm

Enclosure

number of command points 1

Actuator

design of the actuating element Flat buttons

principle of operation of the actuating element momentary contact type

product extension optional

? light source No
? contact module Yes
color of the actuating element white / white
material of the actuating element plastic
shape of the actuating element oval
marking of the actuating element Arrow to the left, arrow to the right
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring Metal, high gloss
color of the front ring silver
General technical data
protection class IP IP66, IP67, IP69(IP69K)
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
operating frequency maximum 3 600 1/h
mechanical service life (switching cycles) typical 2 000 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 10/01/2014
Ambient conditions
ambient temperature
? during operation -25 ... +70 °C
? during storage -40 ... +80 °C
environmental category during operation accord...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1050-3AB66-0AM0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.