

INDUSTRIAL COMPONENT DATA

3SU1050-4JF01-0AA0 SIEMENS Key-operated switch O.M.R, 22 mm, round, metal, shiny, lock number 73033, yellow,..

Brand: SIEMENS | Manufacturer Part Number: 3SU1050-4JF01-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1050-4JF01-0AA0
Catalog number	10504
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-EB76378AC2
Generated	2026-08-06

Product Overview

Key-operated switch O.M.R, 22 mm, round, metal, shiny, lock number 73033, yellow, with 2 keys, 2 switch positions O-I, latching, actuating angle 90°, 10:30h/13:30h, Key removal O

O.M.R KEY SWITCH, 22MM, ROUND, METAL, SHINY, LOCK NO. 73033, AMAR., WITH 2 WRENCHES, 2 POSITIONS O-I, SUSTAINED, 90 DEGREE ANGLE, 10:30H/13:30H, EXTRACTION POSITION O.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Key-operated switch O.M.R, 22 mm, round, metal, shiny, lock number 73033, yellow, with 2 keys, 2 switch positions O-I, latching, actuating angle 90°, 10:30h/13:30h, Key removal O

product brand name SIRIUS ACT

product designation Key-operated switches

design of the product Actuating/signaling element

product type designation 3SU1

product line Metal, shiny, 22 mm

manufacturer's article number of included key 3SU1950-0FM30-0AA0

Actuator

principle of operation of the actuating element latching, 90° (10:30 h/13:30 h)

product extension optional light source No

color
? of the actuating element yellow
material of the actuating element metal
shape of the actuating element Key
outer diameter of the actuating element 29.5 mm
number of switching positions 2
switch position for key distraction O
actuating angle
? clockwise 90°
lock make O.M.R.
key number 73033
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring Metal, high gloss
color of the front ring silver
General technical data
protection class IP IP66, IP67, IP69(IP69K)
? of the terminal IP20
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
operating frequency maximum 1 800 1/h
mechanical service life (switching cycles) typical 300 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 10/...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1050-4JF01-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.