

INDUSTRIAL COMPONENT DATA

3SU1051-1EA20-0AA0 SIEMENS Illuminated mushroom pushbutton, 22 mm, round, metal, shiny, red, 40 mm, 3 switch..

Brand: SIEMENS | Manufacturer Part Number: 3SU1051-1EA20-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1051-1EA20-0AA0
Catalog number	10511
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-8A77DF3946
Generated	2026-08-04

Product Overview

Illuminated mushroom pushbutton, 22 mm, round, metal, shiny, red, 40 mm, 3 switch positions, latches after pushing in, unlatches by pull-to-unlatch mechanism to center position, after pulling out the button Retraction to center position ILLUMINATED MUSHROOM PUSHBUTTON, 22MM, ROUND, METAL, SHINY, RED, 40MM, 3 POSITIONS, LOCKS WHEN PRESSED, TRACTION UNLOCKING IN THE INTERMEDIATE POSITION, AFTER PULLING THE BUTTON IT RETURNS TO THE INTERMEDIATE POSITION.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Illuminated mushroom pushbutton, 22 mm, round, metal, shiny, red, 40 mm, 3 switch positions, latches after pushing in, unlatches by pull-to-unlatch mechanism to center position, after pulling out the button Retraction to center position

product brand name SIRIUS ACT

product designation Mushroom pushbuttons

design of the product Actuating/signaling element

product type designation 3SU1

product line Metal, shiny, 22 mm

Enclosure

number of command points 1

Actuator

design of the actuating element illuminated

principle of operation of the actuating element latching

product extension optional light source Yes

color of the actuating element red

material of the actuating element plastic

shape of the actuating element round

outer diameter of the actuating element 40 mm

type of unlocking device pull-to-unlatch mechanism

number of switching positions 3

Front ring

product component front ring Yes

design of the front ring Standard

material of the front ring Metal, high gloss

color of the front ring silver

General technical data

product function

? EMERGENCY OFF function No

? EMERGENCY STOP function No

protection class IP IP66, IP67, IP69(IP69K)

degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

shock resistance

? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms

vibration resistance

? according to IEC 60068-2-6 10 ... 500 Hz: 5g

operating frequency maximum 1 800 1/h

mechanical service life (switching cycles) typical 300 000

reference code according to I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1051-1EA20-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.