

INDUSTRIAL COMPONENT DATA

3SU1051-1ED20-0AA0 SIEMENS Illuminated mushroom pushbutton, 22 mm, round, metal, shiny, red, 40 mm, 3 switch..

Brand: SIEMENS | Manufacturer Part Number: 3SU1051-1ED20-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1051-1ED20-0AA0
Catalog number	10511
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-27663AA432
Generated	2026-08-05

Product Overview

Illuminated mushroom pushbutton, 22 mm, round, metal, shiny, red, 40 mm, 3 switch positions, after pushing in Retraction to center position, after pulling out the button Retraction to center position
ILLUMINATED MUSHROOM PUSHBUTTON, 22MM, ROUND, METAL, SHINY, RED, 40MM, 3 POSITIONS, AFTER PRESSING IT RETURNS TO INTERMEDIATE POSITION, AFTER PULLING THE BUTTON RETURNS TO INTERMEDIATE POSITION RETURNS TO INTERMEDIATE POSITION.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Illuminated mushroom pushbutton, 22 mm, round, metal, shiny, red, 40 mm, 3 switch positions, after pushing in Retraction to center position, after pulling out the button Retraction to center position
product brand name SIRIUS ACT
product designation Mushroom pushbuttons
design of the product Actuating/signaling element
product type designation 3SU1
product line Metal, shiny, 22 mm
Enclosure

number of command points 1

Actuator

design of the actuating element illuminated

principle of operation of the actuating element momentary contact type

product extension optional light source Yes

color of the actuating element red

material of the actuating element plastic

shape of the actuating element round

outer diameter of the actuating element 40 mm

number of switching positions 3

Front ring

product component front ring Yes

design of the front ring Standard

material of the front ring Metal, high gloss

color of the front ring silver

General technical data

product function

? EMERGENCY OFF function No

? EMERGENCY STOP function No

protection class IP IP66, IP67, IP69(IP69K)

degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

shock resistance

? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms

vibration resistance

? according to IEC 60068-2-6 10 ... 500 Hz: 5g

operating frequency maximum 1 800 1/h

mechanical service life (switching cycles) typical 300 000

reference code according to IEC 81346-2 S

Substance Prohibitance (Date) 10/01/2014

Ambient conditions

a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1051-1ED20-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.