

INDUSTRIAL COMPONENT DATA

3SU1051-3AB61-0AA0 SIEMENS Illuminated twin pushbutton, 22 mm, round, metal, shiny, white, black, pushbutton..

Brand: SIEMENS | Manufacturer Part Number: 3SU1051-3AB61-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1051-3AB61-0AA0
Catalog number	10513
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-EE61E34B86
Generated	2026-08-04

Product Overview

Illuminated twin pushbutton, 22 mm, round, metal, shiny, white, black, pushbuttons, flat
DOUBLE ILLUMINATED PUSH BUTTON, 22MM, ROUND, METAL, GLOSSY, WHITE, BLACK, BUTTONS, FLUSH,.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

Technical data

Illuminated twin pushbutton, 22 mm, round, metal, shiny, white, black, pushbuttons, flat

product brand name SIRIUS ACT

product designation Twin pushbuttons

design of the product Actuating/signaling element

product type designation 3SU1

product line Metal, shiny, 22 mm

Enclosure

number of command points 1

Actuator

design of the actuating element Flat buttons, illuminated

principle of operation of the actuating element momentary contact type

product extension optional

? light source Yes

? contact module Yes

color of the actuating element white / black

material of the actuating element plastic

shape of the actuating element oval

Front ring

product component front ring Yes

design of the front ring Standard

material of the front ring Metal, high gloss

color of the front ring silver

General technical data

protection class IP IP66, IP67, IP69(IP69K)

degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

shock resistance

? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms

vibration resistance

? according to IEC 60068-2-6 10 ... 500 Hz: 5g

operating frequency maximum 3 600 1/h

mechanical service life (switching cycles) typical 2 000 000

reference code according to IEC 81346-2 S

Substance Prohibitance (Date) 10/01/2014

Ambient conditions

ambient temperature

? during operation -25 ... +70 °C

? during storage -40 ... +80 °C

environmental category during operation according to IEC 60721 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%)

Inst...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1051-3AB61-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.