

INDUSTRIAL COMPONENT DATA

3SU1052-2BL40-0AA0 SIEMENS Selector switch, illuminable, 22 mm, round, metal, shiny, green, selector switch,...

Brand: SIEMENS | Manufacturer Part Number: 3SU1052-2BL40-0AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1052-2BL40-0AA0
Catalog number	10522
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-5EE4B4DB24
Generated	2026-08-04

Product Overview

Selector switch, illuminable, 22 mm, round, metal, shiny, green, selector switch, short, 3 switch positions I-O-II, latching, actuating angle 2x45°, 10:30h/12h/13:30h

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

Technical data

Selector switch, illuminable, 22 mm, round, metal, shiny, green, selector switch, short, 3 switch positions I-O-II, latching, actuating angle 2x45°, 10:30h/12h/13:30h

product brand name SIRIUS ACT

product designation Selector switches

design of the product Actuating/signaling element

product type designation 3SU1

product line Metal, shiny, 22 mm

Enclosure

number of command points 1

Actuator

design of the actuating element Selector, short

principle of operation of the actuating element latching, 2x45° (10:30 h/12 h/13:30 h)

product extension optional

? light source Yes
? contact module Yes
color of the actuating element green
material of the actuating element plastic
shape of the actuating element Handle
outer diameter of the actuating element 32.3 mm
number of switching positions 3
actuating angle
? clockwise 45°
? anticlockwise 45°
Front ring
product component front ring Yes
design of the front ring standard
material of the front ring Metal, high gloss
color of the front ring silver
General technical data
protection class IP IP66, IP67, IP69(IP69K)
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
operating frequency maximum 1 800 1/h
mechanical service life (switching cycles) typical 1 000 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 10/01/2014
Safety related data
B10 valu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1052-2BL40-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.