

INDUSTRIAL COMPONENT DATA

3SU1100-0AB30-1BA0 SIEMENS Pushbutton, 22 mm, round, plastic, yellow, pushbutton, flat, momentary contact ty..

Brand: SIEMENS | Manufacturer Part Number: 3SU1100-0AB30-1BA0



Manufacturer	SIEMENS
MPN / Reference	3SU1100-0AB30-1BA0
Catalog number	11000
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-9D72C9DD93
Generated	2026-08-02

Product Overview

Pushbutton, 22 mm, round, plastic, yellow, pushbutton, flat, momentary contact type, with holder 1 NO, screw terminal
PUSH BUTTON, 22MM, ROUND, PLASTIC, YELLOW, BUTTON, FLUSH, MOMENTARY, WITH SUPPORT, 1NA, SCREW TERMINALS.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Pushbutton, 22 mm, round, plastic, yellow, pushbutton, flat, momentary contact type, with holder 1 NO, screw terminal

product brand name SIRIUS ACT

product designation Pushbuttons

design of the product Complete unit

product type designation 3SU1

product line Plastic, black, 22 mm

manufacturer's article number

? of supplied contact module at position 1 3SU1400-1AA10-1BA0

? of the supplied holder 3SU1550-0AA10-0AA0

? of the supplied actuator 3SU1000-0AB30-0AA0

number of command points 1

Actuator

design of the actuating element Button, flat
principle of operation of the actuating element momentary contact type
product extension optional light source No
color of the actuating element yellow
material of the actuating element plastic
shape of the actuating element round
outer diameter of the actuating element 29.45 mm
number of contact modules 1
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black
Holder
material of the holder Plastic
Display
number of LED modules 0
General technical data
product function positive opening No
product component light source No
insulation voltage rated value 500 V
degree of pollution 3
type of voltage of the operating voltage AC/DC
surge voltage resistance rated value 6 kV
protection class IP IP66, IP67, IP69(IP69K)
? of the terminal IP20
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
? according to IEC 60068-2-27 sin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1100-0AB30-1BA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.