

INDUSTRIAL COMPONENT DATA

3SU1106-0AB60-1BA0 SIEMENS Illuminated pushbutton, 22 mm, round, plastic, white, pushbutton, flat, momentary..

Brand: SIEMENS | Manufacturer Part Number: 3SU1106-0AB60-1BA0



Manufacturer	SIEMENS
MPN / Reference	3SU1106-0AB60-1BA0
Catalog number	11060
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-D4EF60A634
Generated	2026-08-01

Product Overview

Illuminated pushbutton, 22 mm, round, plastic, white, pushbutton, flat, momentary contact type, with holder, 1 NO, LED module with integrated LED 230 V AC, screw terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Illuminated pushbutton, 22 mm, round, plastic, white, pushbutton, flat, momentary contact type, with holder, 1 NO, LED module with integrated LED 230 V AC, screw terminal

product brand name SIRIUS ACT

product designation Illuminated pushbuttons

design of the product Complete unit

product type designation 3SU1

product line Plastic, black, 22 mm

manufacturer's article number

? of supplied contact module at position 1 3SU1400-1AA10-1BA0

? of supplied LED module 3SU1401-1BF60-1AA0

? of the supplied holder 3SU1550-0AA10-0AA0

? of the supplied actuator 3SU1001-0AB60-0AA0

number of command points 1

Actuator

design of the actuating element Button, flat
principle of operation of the actuating element momentary contact type
product extension optional light source Yes
color of the actuating element white
material of the actuating element plastic
shape of the actuating element round
outer diameter of the actuating element 29.45 mm
number of contact modules 1

Front ring

product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black

Holder

material of the holder Plastic

Display

number of LED modules 1

General technical data

product function positive opening No
product component light source Yes
insulation voltage rated value 320 V
degree of pollution 3
type of voltage of the operating voltage AC/DC
surge voltage resistance rated value 4 kV
protection class IP IP66, IP67, IP69(IP69K)
? of the terminal IP20....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1106-0AB60-1BA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.