

INDUSTRIAL COMPONENT DATA

3SU1106-6AA50-1AA0 SIEMENS Indicator lights, 22 mm, round, plastic, blue, lens, smooth, with holder, LED mod..

Brand: SIEMENS | Manufacturer Part Number: 3SU1106-6AA50-1AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1106-6AA50-1AA0
Catalog number	11066
Category	Indicator light complete
Minimum order	1 Pcs
Document ID	EO-E663D8D432
Generated	2026-08-03

Product Overview

Indicator lights, 22 mm, round, plastic, blue, lens, smooth, with holder, LED module, with integrated LED 230 V AC, screw terminal

SIGNALING LAMP 22MM, ROUND, PLASTIC, BLUE, LENS, SMOOTH, WITH SUPPORT, LED MODULE, WITH INTEGRATED LED 230V AC, SCREW TERMINALS. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

Additional Product Information

Technical data

Indicator lights, 22 mm, round, plastic, blue, lens, smooth, with holder, LED module, with integrated LED 230 V AC, screw terminal

product brand name SIRIUS ACT

product designation Indicator lights

design of the product Complete unit

product type designation 3SU1

product line Plastic, black, 22 mm

manufacturer's article number

? of supplied LED module 3SU1401-1BF50-1AA0

? of the supplied holder 3SU1550-0AA10-0AA0

? of supplied repeater 3SU1001-6AA50-0AA0

Enclosure

number of command points 1

Actuator

product extension optional light source Yes

color

? of the actuating element blue

material of the actuating element plastic

shape of the actuating element round

outer diameter of the actuating element 29.45 mm

Front ring

product component front ring No

Holder

material of the holder Plastic

Display

number of LED modules 1

General technical data

product component light source Yes

insulation voltage rated value 320 V

degree of pollution 3

surge voltage resistance rated value 4 kV

protection class IP IP66, IP67, IP69(IP69K)

? of the terminal IP20

degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

shock resistance

? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms

? for railway applications according to EN 61373 Category 1, Class B

vibration resistance

? according to IEC 60068-2-6 10 ... 500 Hz: 5g

? for railway applications according to EN 61373 Category 1, Class B

reference code according to IEC 81346-2 P

Substance Prohibitance (Date) 10/01/2014

S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1106-6AA50-1AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.