

INDUSTRIAL COMPONENT DATA

3SU1150-0AB60-3BA0 SIEMENS Pushbutton, 22 mm, round, metal, shiny, white, pushbutton, flat, momentary contac..

Brand: SIEMENS | Manufacturer Part Number: 3SU1150-0AB60-3BA0



Manufacturer	SIEMENS
MPN / Reference	3SU1150-0AB60-3BA0
Catalog number	11500
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-6D2E1F8333
Generated	2026-08-03

Product Overview

Pushbutton, 22 mm, round, metal, shiny, white, pushbutton, flat, momentary contact type, with holder, 1 NO, Spring-type terminal

PUSH BUTTON, 22MM, ROUND, METAL, GLOSSY, WHITE, BUTTON, FLUSH, MOMENTARY, WITH SUPPORT, 1NA, SPRING TERMINALS.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

Technical data

Pushbutton, 22 mm, round, metal, shiny, white, pushbutton, flat, momentary contact type, with holder, 1 NO, Spring-type terminal

product brand name SIRIUS ACT

product designation Pushbuttons

design of the product Complete unit

product type designation 3SU1

product line Metal, shiny, 22 mm

manufacturer's article number

? of supplied contact module at position 1 3SU1400-1AA10-3BA0

? of the supplied holder 3SU1550-0AA10-0AA0

? of the supplied actuator 3SU1050-0AB60-0AA0

number of command points 1

Actuator

design of the actuating element Button, flat

principle of operation of the actuating element momentary contact type

product extension optional light source No

color of the actuating element white

material of the actuating element plastic

shape of the actuating element round

outer diameter of the actuating element 29.45 mm

number of contact modules 1

Front ring

product component front ring Yes

design of the front ring Standard

material of the front ring Metal, high gloss

color of the front ring silver

Holder

material of the holder Plastic

Display

number of LED modules 0

General technical data

product function positive opening No

product component light source No

insulation voltage rated value 500 V

degree of pollution 3

type of voltage of the operating voltage AC/DC

surge voltage resistance rated value 6 kV

protection class IP IP66, IP67, IP69(IP69K)

? of the terminal IP20

degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

shock resistance

? according to...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1150-0AB60-3BA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.