

INDUSTRIAL COMPONENT DATA

3SU1152-6AA60-1AA0 SIEMENS Indicator lights, 22 mm, round, metal, shiny, white, lens, smooth, with holder, L..

Brand: SIEMENS | Manufacturer Part Number: 3SU1152-6AA60-1AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1152-6AA60-1AA0
Catalog number	11526
Category	Indicator light complete
Minimum order	1 Pcs
Document ID	EO-18ED525CFD
Generated	2026-08-04

Product Overview

Indicator lights, 22 mm, round, metal, shiny, white, lens, smooth, with holder, LED module with integrated LED 24 V AC/DC, screw terminal

SIGNALING LAMP, 22MM, ROUND, METAL, BRIGHT, WHITE, LENS, SMOOTH, WITH STAND, LED MODULE, WITH INTEGRATED LED 24V AC/DC, SCREW TERMINALS.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Indicator lights, 22 mm, round, metal, shiny, white, lens, smooth, with holder, LED module with integrated LED 24 V AC/DC, screw terminal

product brand name SIRIUS ACT

product designation Indicator lights

design of the product Complete unit

product type designation 3SU1

product line Metal, shiny, 22 mm

manufacturer's article number

? of supplied LED module 3SU1401-1BB60-1AA0

? of the supplied holder 3SU1550-0AA10-0AA0

? of supplied repeater 3SU1051-6AA60-0AA0

Enclosure

number of command points 1

Actuator

product extension optional light source Yes

color

? of the actuating element white

material of the actuating element plastic

shape of the actuating element round

outer diameter of the actuating element 29.45 mm

Front ring

product component front ring No

Holder

material of the holder Plastic

Display

number of LED modules 1

General technical data

product component light source Yes

insulation voltage rated value 320 V

degree of pollution 3

surge voltage resistance rated value 4 kV

protection class IP IP66, IP67, IP69(IP69K)

? of the terminal IP20

degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

shock resistance

? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms

vibration resistance

? according to IEC 60068-2-6 10 ... 500 Hz: 5g

reference code according to IEC 81346-2 P

Substance Prohibitance (Date) 10/01/2014

Supply voltage

type of voltage of the supply voltage of the light source AC/DC

supply voltage of the light source at AC

? at 50 Hz ra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1152-6AA60-1AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.