

INDUSTRIAL COMPONENT DATA

3SU1152-6AA70-3AA0 SIEMENS Indicator lights, 22 mm, round, metal, shiny, clear, lens, smooth, with holder, L..

Brand: SIEMENS | Manufacturer Part Number: 3SU1152-6AA70-3AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1152-6AA70-3AA0
Catalog number	11526
Category	Indicator light complete
Minimum order	1 Pcs
Document ID	EO-7AD2AC2D9E
Generated	2026-08-05

Product Overview

Indicator lights, 22 mm, round, metal, shiny, clear, lens, smooth, with holder, LED module with integrated LED 24 V AC/DC, Spring-type terminal

SIGNALING LAMP, 22MM, ROUND, METAL, GLOSSY, TRANSPARENT, LENS, SMOOTH, WITH SUPPORT, LED MODULE, WITH INTEGRATED LED 24V AC / DC, SPRING TERMINALS. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Indicator lights, 22 mm, round, metal, shiny, clear, lens, smooth, with holder, LED module with integrated LED 24 V AC/DC, Spring-type terminal

product brand name SIRIUS ACT

product designation Indicator lights

design of the product Complete unit

product type designation 3SU1

product line Metal, shiny, 22 mm

manufacturer's article number

? of supplied LED module 3SU1401-1BB60-3AA0

? of the supplied holder 3SU1550-0AA10-0AA0

? of supplied repeater 3SU1051-6AA70-0AA0
Enclosure
number of command points 1
Actuator
product extension optional light source Yes
color
? of the actuating element clear
material of the actuating element plastic
shape of the actuating element round
outer diameter of the actuating element 29.45 mm
Front ring
product component front ring No
Holder
material of the holder Plastic
Display
number of LED modules 1
General technical data
product component light source Yes
insulation voltage rated value 320 V
degree of pollution 3
surge voltage resistance rated value 4 kV
protection class IP IP66, IP67, IP69(IP69K)
? of the terminal IP20
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
reference code according to IEC 81346-2 P
Substance Prohibitance (Date) 10/01/2014
Supply voltage
type of voltage of the supply voltage of the light source AC/DC
supply voltage of the light source at AC
? at 50...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1152-6AA70-3AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.