

## INDUSTRIAL COMPONENT DATA

# 3SU1156-0AB50-3BA0 SIEMENS Illuminated pushbutton, 22 mm, round, metal, shiny, blue, pushbutton, flat, momen..

Brand: SIEMENS | Manufacturer Part Number: 3SU1156-0AB50-3BA0



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | SIEMENS               |
| MPN / Reference | 3SU1156-0AB50-3BA0    |
| Catalog number  | 11560                 |
| Category        | Push button, complete |
| Minimum order   | 1 Pcs                 |
| Document ID     | EO-3950768076         |
| Generated       | 2026-08-04            |

## Product Overview

Illuminated pushbutton, 22 mm, round, metal, shiny, blue, pushbutton, flat, momentary contact type, with holder, 1 NO, LED module with integrated LED 230 V AC, Spring-type terminal

ILLUMINATED PUSH BUTTON, 22MM, ROUND, METAL, GLOSSY, BLUE, BUTTON, FLUSH, MOMENTARY, WITH SUPPORT, 1NA, LED MODULE, WITH INTEGRATED LED 230V AC, SPRING TERMINALS.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                     |
|--------------|---------------------------------------------------------------------|
| Catalog path | SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices |
|--------------|---------------------------------------------------------------------|

## Additional Product Information

## Technical data

Illuminated pushbutton, 22 mm, round, metal, shiny, blue, pushbutton, flat, momentary contact type, with holder, 1 NO, LED module with integrated LED 230 V AC, Spring-type terminal

product brand name SIRIUS ACT

product designation Illuminated pushbuttons

design of the product Complete unit

product type designation 3SU1

product line Metal, shiny, 22 mm

manufacturer's article number

? of supplied contact module at position 1 3SU1400-1AA10-3BA0

? of supplied LED module 3SU1401-1BF50-3AA0

? of the supplied holder 3SU1550-0AA10-0AA0

? of the supplied actuator 3SU1051-0AB50-0AA0

number of command points 1

Actuator

design of the actuating element Button, flat

principle of operation of the actuating element momentary contact type

product extension optional light source Yes

color of the actuating element blue

material of the actuating element plastic

shape of the actuating element round

outer diameter of the actuating element 29.45 mm

number of contact modules 1

Front ring

product component front ring Yes

design of the front ring Standard

material of the front ring Metal, high gloss

color of the front ring silver

Holder

material of the holder Plastic

Display

number of LED modules 1

General technical data

product function positive opening No

product component light source Yes

insulation voltage rated value 320 V

degree of pollution 3

type of voltage of the operating voltage AC/DC

surge voltage resistance rated value 4 kV

protection class IP IP66, IP67, IP69(IP69K)

? of....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1156-0AB50-3BA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.