

## INDUSTRIAL COMPONENT DATA

# 3SU1200-0EB40-0AA0 SIEMENS Pushbutton, compact, with extended stroke (12 mm), 22 mm, round, plastic, green, ..

Brand: SIEMENS | Manufacturer Part Number: 3SU1200-0EB40-0AA0



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 3SU1200-0EB40-0AA0            |
| Catalog number  | 12000                         |
| Category        | Front element for push button |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-F19F312F36                 |
| Generated       | 2026-08-02                    |

## Product Overview

Pushbutton, compact, with extended stroke (12 mm), 22 mm, round, plastic, green, pushbutton, flat, momentary contact type, with holder

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

## Additional Product Information

## Technical data

Pushbutton, compact, with extended stroke (12 mm), 22 mm, round, plastic, green, pushbutton, flat, momentary contact type, with holder

product brand name SIRIUS ACT

product designation Pushbuttons

design of the product Complete unit

product type designation 3SU1

product line Plastic, black, 22 mm

Enclosure

number of command points 1

Actuator

design of the actuating element Flat button with extended stroke

principle of operation of the actuating element momentary contact type

product extension optional

? light source No  
? contact module Yes  
color of the actuating element green  
material of the actuating element plastic  
shape of the actuating element round  
outer diameter of the actuating element 29.5 mm  
Front ring  
product component front ring Yes  
design of the front ring Standard  
material of the front ring plastic  
color of the front ring black  
General technical data  
protection class IP IP66, IP67, IP69(IP69K)  
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13  
shock resistance  
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms  
? for railway applications according to EN 61373 Category 1, Class B  
vibration resistance  
? according to IEC 60068-2-6 10 ... 500 Hz: 5g  
? for railway applications according to EN 61373 Category 1, Class B  
operating frequency maximum 3 600 1/h  
mechanical service life (switching cycles) typical 5 000 000  
reference code according to IEC 81346-2 S  
Substance Prohibitance (Date) 10/01/2014  
Ambient conditions  
ambient temperatu...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1200-0EB40-0AA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.