

INDUSTRIAL COMPONENT DATA

3SU1200-2PV10-1AA0 SIEMENS Potentiometer, compact, 22 mm, round, plastic, black, 470k ohm, with holder, scre..

Brand: SIEMENS | Manufacturer Part Number: 3SU1200-2PV10-1AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1200-2PV10-1AA0
Catalog number	12002
Category	Potentiometer for command devices
Minimum order	1 Pcs
Document ID	EO-25006A866F
Generated	2026-08-06

Product Overview

Potentiometer, compact, 22 mm, round, plastic, black, 470k ohm, with holder, screw terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

Additional Product Information

Technical data

Potentiometer, compact, 22 mm, round, plastic, black, 470k ohm, with holder, screw terminal

product brand name SIRIUS ACT

product designation Potentiometers

design of the product Compact unit

product type designation 3SU1

product line Plastic, black, 22 mm

manufacturer's article number of the supplied holder 3SU1550-0AA10-0AA0

Enclosure

number of command points 1

Actuator

design of the actuating element Rotary knob

principle of operation of the actuating element Infinitely variable adjustment, angle of rotation 280°

color of the actuating element black

material of the actuating element plastic

shape of the actuating element round
outer diameter of the actuating element 30 mm
Maximum deflection angle [°] 280°
Front ring
product component front ring No
Holder
material of the holder Plastic
General technical data
insulation voltage rated value 500 V
degree of pollution 3
protection class IP IP66, IP67, IP69(IP69K)
? of the terminal IP20, clamping screw tightened
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
? for railway applications according to EN 61373 Category 1, Class B
mechanical service life (switching cycles) typical 25 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 01/01/2016
Connections/ Terminals....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1200-2PV10-1AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.