

INDUSTRIAL COMPONENT DATA

3SU1200-6KB10-1AA0 SIEMENS acoustic signal device, compact, 22 mm, round, plastic, black, Continuous tone 2...

Brand: SIEMENS | Manufacturer Part Number: 3SU1200-6KB10-1AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1200-6KB10-1AA0
Catalog number	12006
Category	Acoustic indicator
Minimum order	1 Pcs
Document ID	EO-5C5AD332BB
Generated	2026-08-06

Product Overview

acoustic signal device, compact, 22 mm, round, plastic, black, Continuous tone 2.4 kHz, IP40, Sound pressure min. 80 dB/10 cm, with holder, Operating voltage 24 V AC/DC, screw terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

Additional Product Information

Technical data

acoustic signal device, compact, 22 mm, round, plastic, black, Continuous tone 2.4 kHz, IP40, Sound pressure min. 80 dB/10 cm, with holder, Operating voltage 24 V AC/DC, screw terminal

product brand name SIRIUS ACT

product designation Acoustic signaling device

design of the product Compact unit

product type designation 3SU1

product line Plastic, black, 22 mm

manufacturer's article number of the supplied holder 3SU1550-0AA10-0AA0

Enclosure

number of command points 1

Actuator

color of the actuating element black

material of the actuating element plastic

shape of the actuating element round
outer diameter of the actuating element 29.5 mm
Front ring
product component front ring No
Holder
material of the holder Plastic
General technical data
loudness level at 10 cm distance 80 dB
insulation voltage rated value 320 V
degree of pollution 3
surge voltage resistance rated value 4 kV
consumed current at rated value of operating voltage maximum 28 mA
protection class IP IP40
? of the terminal IP20, clamping screw tightened
degree of protection NEMA rating 1
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
? for railway applications according to EN 61373 Category 1, Class B
reference code according to IEC 81346-2 P
Substance Prohibitance (Date) 10/01/2014
relative positive tolerance of the operating voltage...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1200-6KB10-1AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.