

INDUSTRIAL COMPONENT DATA

3SU1250-2PS10-1AA0 SIEMENS Potentiometer, compact, 22 mm, round, metal, black, 10k ohm, with holder, screw t..

Brand: SIEMENS | Manufacturer Part Number: 3SU1250-2PS10-1AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1250-2PS10-1AA0
Catalog number	12502
Category	Potentiometer for command devices
Minimum order	1 Pcs
Document ID	EO-D9E952B21B
Generated	2026-08-03

Product Overview

Potentiometer, compact, 22 mm, round, metal, black, 10k ohm, with holder, screw terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

Additional Product Information

ETIM: EC001027 - Potentiometer for command devices

Value Unit

Resistance (EF002431) 10000.0 Ohm

Power consumption (EF000346) 1.0 W

Hole diameter (EF000079) 22.3 mm

Number of revolutions (EF006943) ['270', '270']

Type of electric connection (EF003961) Screw connection

Degree of protection (IP) (EF005474) Other

Degree of protection (NEMA) (EF011959) NEMA 1, 2, 3, 3R, 4, 4X, 12, 13

Potentiometer, compact, 22 mm, round, metal, black, 10k ohm, with holder, screw terminal

Product brand name SIRIUS ACT

Product designation Potentiometers

Design of the product Compact unit

Product type designation 3SU1

Product line Metal, shiny, 22 mm

Manufacturer's article number

? of the supplied holder 3SU1550-0AA10-0AA0

Enclosure

Number of command points 1

Actuator

Design of the operating mechanism Rotary knob

Manner of function of the actuating element Infinitely variable adjustment, angle of rotation 280°

Color

? of the actuating element black

Material of the actuating element plastic

Shape of the actuating element round

Outer diameter of the actuating element 30 mm

Maximum deflection angle [°] 280°

Front ring

Product component front ring No

Holder

Material of the holder Metal

General technical data

Insulation voltage

? rated value 500 V

Degree of pollution 3

Protection class IP IP66, IP67, IP69(IP69K)

? of the terminal IP20

Degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13

Shock resistance

? acc. to IEC 60068-2-27 Sinusoidal half-wave 50 g / 11 ms

Vibration resistance

? acc. to IEC 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1250-2PS10-1AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.