

INDUSTRIAL COMPONENT DATA

3SU1250-2PT10-1AA0 SIEMENS Potentiometer, compact, 22 mm, round, metal, black, 47k ohm, with holder, screw t..

Brand: SIEMENS | Manufacturer Part Number: 3SU1250-2PT10-1AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1250-2PT10-1AA0
Catalog number	12502
Category	Potentiometer for command devices
Minimum order	1 Pcs
Document ID	EO-86935C5ABD
Generated	2026-08-06

Product Overview

Potentiometer, compact, 22 mm, round, metal, black, 47k ohm, with holder, screw terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices

Additional Product Information

ETIM: EC001027 - Potentiometer for command devices

Value Unit

Resistance (EF002431) 47000.0 Ohm

Power consumption (EF000346) 1.0 W

Hole diameter (EF000079) 22.3 mm

Number of revolutions (EF006943) ['270', '270']

Type of electric connection (EF003961) Screw connection

Degree of protection (IP) (EF005474) Other

Degree of protection (NEMA) (EF011959) NEMA 1, 2, 3, 3R, 4, 4X, 12, 13

Potentiometer, compact, 22 mm, round, metal, black, 47k ohm, with holder, screw terminal

Product brand name SIRIUS ACT

Product designation Potentiometers

Design of the product Compact unit

Product type designation 3SU1

Product line Metal, shiny, 22 mm

Manufacturer's article number
? of the supplied holder 3SU1550-0AA10-0AA0
Enclosure
Number of command points 1
Actuator
Design of the operating mechanism Rotary knob
Manner of function of the actuating element Infinitely variable adjustment, angle of rotation 280°
Color
? of the actuating element black
Material of the actuating element plastic
Shape of the actuating element round
Outer diameter of the actuating element 30 mm
Maximum deflection angle [°] 280°
Front ring
Product component front ring No
Holder
Material of the holder Metal
General technical data
Insulation voltage
? rated value 500 V
Degree of pollution 3
Protection class IP IP66, IP67, IP69(IP69K)
? of the terminal IP20
Degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
Shock resistance
? acc. to IEC 60068-2-27 Sinusoidal half-wave 50 g / 11 ms
Vibration resistance
? acc. to IEC 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1250-2PT10-1AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.