

INDUSTRIAL COMPONENT DATA

3SU1250-6KC10-1AA0 SIEMENS acoustic signal device, compact, 22 mm, round, Metal, black, Continuous tone 2.4 ..

Brand: SIEMENS | Manufacturer Part Number: 3SU1250-6KC10-1AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1250-6KC10-1AA0
Catalog number	12506
Category	Acoustic indicator
Minimum order	1 Pcs
Document ID	EO-9F5E6FD25C
Generated	2026-08-06

Product Overview

acoustic signal device, compact, 22 mm, round, Metal, black, Continuous tone 2.4 kHz, IP40, Sound pressure min. 80 dB/10 cm, with holder, Operating voltage 110 V AC, screw terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

ETIM: EC001026 - Acoustic indicator

Value Unit

Voltage type (EF000187) -

Operating voltage at AC 60 Hz (EF008207) - V

Operating voltage at AC 50 Hz (EF008206) - V

Operating voltage at DC (EF008208) - V

Type of acoustic signal (EF002751) Continuous tone

Loudness (EF000144) 90 dB

acoustic signal device, compact, 22 mm, round, Metal, black, Continuous tone 2.4 kHz, IP40, Sound pressure min. 80 dB/10 cm, with holder, Operating voltage 110 V AC, screw terminal

Product brand name SIRIUS ACT

Product designation Acoustic signaling device

Design of the product Compact unit

Product type designation 3SU1

Product line Metal, shiny, 22 mm
Manufacturer's article number
? of the supplied holder 3SU1550-0AA10-0AA0
Enclosure
Number of command points 1
Actuator
Color
? of the actuating element black
Material of the actuating element plastic
Shape of the actuating element round
Outer diameter of the actuating element 29.5 mm
Front ring
Product component front ring No
Holder
Material of the holder Metal
General technical data
Loudness level at 10 cm distance 80 dB
Insulation voltage
? rated value 320 V
Degree of pollution 3
Surge voltage resistance rated value 4 kV
Consumed current
? at rated value of operating voltage maximum 32 mA
Protection class IP IP40
? of the terminal IP20
Degree of protection NEMA rating 1
Shock resistance
? acc. to IEC 60068-2-27 Sinusoidal half-wave 50 g / 11 ms
Vibration resistance
? acc. to IEC 60068-2-6 10 ... 500 Hz: 5g
Reference code acc. to DIN EN 81346-2 P
Refe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1250-6KC10-1AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.