


INDUSTRIAL COMPONENT DATA

3SU1400-1AA10-3GA0 SIEMENS Contact module with 2 contact elements, 1 NO leading + 1 NC lagging, spring-type ..

Brand: SIEMENS | Manufacturer Part Number: 3SU1400-1AA10-3GA0



Manufacturer	SIEMENS
MPN / Reference	3SU1400-1AA10-3GA0
Catalog number	14001
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-D375EB16EE
Generated	2026-08-03

Product Overview

Contact module with 2 contact elements, 1 NO leading + 1 NC lagging, spring-type terminal, for front plate mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

ETIM: EC000041 - Auxiliary contact block

Value Unit

Lamp holder (EF000048) -

Model (EF000010) -

Mounting method (EF000003) -

Number of fault-signal switches (EF007613) -

Number of contacts as change-over contact (EF008257) 1

Number of contacts as normally open contact (EF008256) 1

Number of contacts as normally closed contact (EF008255) 1

Rated operation current Ie at AC-15, 230 V (EF001385) 4 A

Type of electric connection (EF003961) Spring clamp connection

Contact module with 2 contact elements, 1 NO leading + 1 NC lagging, spring-type terminal, for front plate mounting

Product brand name SIRIUS ACT

Product designation Contact module

Product type designation 3SU1

General technical data

Product function

? positive opening Yes

Insulation voltage

? rated value 500 V

Degree of pollution 3

Type of voltage

? of the operating voltage AC/DC

? of the input voltage AC/DC

Surge voltage resistance rated value 6 kV

Protection class IP

? of the enclosure IP40

? of the terminal IP20

Shock resistance

? acc. to IEC 60068-2-27 Sinusoidal half-wave 50 g / 11 ms

? for railway applications acc. to DIN EN 61373 Category 1, Class B

Vibration resistance

? acc. to IEC 60068-2-6 10 ... 500 Hz: 5g

? for railway applications acc. to DIN EN 61373 Category 1, Class B

Operating frequency maximum 3 600 1/h

Mechanical service life (switching cycles)

? typical 10 000 000

Electrical endurance (switching cycles)

? typical 10 000 000

Thermal current 10 A

Reference code acc. to DIN EN 81346-2 S

Reference code a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1400-1AA10-3GA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.