

INDUSTRIAL COMPONENT DATA

3SU1400-1AA10-3LA0 SIEMENS Contact module with 1 contact element, 1 NO, gold-plated contacts, spring-type te..

Brand: SIEMENS | Manufacturer Part Number: 3SU1400-1AA10-3LA0



Manufacturer	SIEMENS
MPN / Reference	3SU1400-1AA10-3LA0
Catalog number	14001
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-9E1BF18A47
Generated	2026-08-05

Product Overview

Contact module with 1 contact element, 1 NO, gold-plated contacts, spring-type terminal, for front plate mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

Technical data

Contact module with 1 contact element, 1 NO, gold-plated contacts, spring-type terminal, for front plate mounting

product brand name SIRIUS ACT

product designation Contact module

product type designation 3SU1

Contact block/ lampholder

socket design other

General technical data

product function positive opening No

insulation voltage rated value 500 V

degree of pollution 3

type of voltage

? of the operating voltage AC/DC

? of the input voltage AC/DC

surge voltage resistance rated value 6 kV

protection class IP

? of the enclosure IP40

? of the terminal IP20

shock resistance

? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms

? for railway applications according to EN 61373 Category 1, Class B

vibration resistance

? according to IEC 60068-2-6 10 ... 500 Hz: 5g

? for railway applications according to EN 61373 Category 1, Class B

operating frequency maximum 3 600 1/h

mechanical service life (switching cycles) typical 10 000 000

electrical endurance (switching cycles) typical 10 000 000

thermal current 10 A

reference code according to IEC 81346-2 S

continuous current of the C characteristic MCB 10 A

Substance Prohibitance (Date) 10/01/2014

operating voltage

? at AC

- at 50 Hz rated value 5 ... 500 V

- at 60 Hz rated value 5 ... 500 V

? at DC rated value 5 ... 500 V

Power Electronics

contact reliability One maloperation per 100 million (17 V, 5 mA), one maloperation per 10 million (5 V, 1 mA)

Auxiliary circuit

design of the contact of auxiliary contacts Gol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1400-1AA10-3LA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.