

INDUSTRIAL COMPONENT DATA

3SU1400-1LK10-1BA1 SIEMENS SIRIUS ACT with PROFINET: standard interface module 24 V DC, screw terminal, fron..

Brand: SIEMENS | Manufacturer Part Number: 3SU1400-1LK10-1BA1



Manufacturer	SIEMENS
MPN / Reference	3SU1400-1LK10-1BA1
Catalog number	10000
Category	Accessories/spare parts for command devices
Minimum order	1 Pcs
Document ID	EO-36CA1229CE
Generated	2026-08-02

Product Overview

SIRIUS ACT with PROFINET: standard interface module 24 V DC, screw terminal, front plate mounting 1 to 20 terminal modules connectable with additional 1 DQ + 4 DI + 1 AI

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

SIRIUS ACT with PROFINET: standard interface module 24 V DC, screw terminal, front plate mounting 1 to 20 terminal modules connectable with additional 1 DQ + 4 DI + 1 AI

product brand name SIRIUS ACT

product designation Interface module for PROFINET

product type designation 3SU1

Display

display version

? for diagnostic function: Supply voltage monitoring power LED Yes

? status Tx/Rx link Yes

General technical data

product function

? reverse polarity protection Yes

? diagnostics function Yes

? alarms Yes
? I&M data Yes; I&M0 ... I&M3
firmware version 2.1.1
hardware version 1
configuration function with dataset Yes
software version with STEP 7 in the TIA Portal required Integrated in TIA Portal Version 14 SP1 or higher (HSP for V13 and V14)
number of units per rack maximum 20
number of submodules per station maximum 24
power loss [W] typical 0.67 W
insulation voltage rated value 30 V
degree of pollution 3
type of voltage
? of the operating voltage DC
? of the input voltage DC
surge voltage resistance rated value 0.8 kV
consumed current
? maximum 100 mA
? rated value 28 mA
protection class IP IP20, clamping screw tightened
reference code according to IEC 81346-2 K
Substance Prohibitance (Date) 12/19/2016
operating voltage rated value 20.4 V
I²t value 0.008 A²·s
Supply voltage
supply voltage at DC rated value 24 V
Communication/ Protocol
protocol is supported
? PROFINET IO protocol Yes
? PROFIsafe protocol No
product function at the Ethernet interface
? Autocrosso...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1400-1LK10-1BA1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.