

INDUSTRIAL COMPONENT DATA

3SU1401-1BB20-1AA0 SIEMENS LED module with integrated LED 24 V AC/DC, red, screw terminal, for front plate m..

Brand: SIEMENS | Manufacturer Part Number: 3SU1401-1BB20-1AA0



Manufacturer	SIEMENS
MPN / Reference	3SU1401-1BB20-1AA0
Catalog number	14011
Category	Lamp holder block for control circuit devices
Minimum order	5 Pcs
Document ID	EO-B3E4B07110
Generated	2026-08-05

Product Overview

LED module with integrated LED 24 V AC/DC, red, screw terminal, for front plate mounting, Minimum order quantity 5 or a multiple thereof

LED MODULE WITH INTEGRATED LED 24V AC/DC, RED, SCREW TERMINALS, FOR FIXING ON FRONT PLATE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

LED module with integrated LED 24 V AC/DC, red, screw terminal, for front plate mounting, Minimum order quantity 5 or a multiple thereof

product brand name SIRIUS ACT

product designation LED module

product type designation 3SU1

General technical data

product component

? diode Yes

? lamp transformer No

? light source Yes

? series resistor No

insulation voltage rated value 320 V

degree of pollution 3
type of voltage of the operating voltage AC/DC
? for actuation AC/DC
surge voltage resistance rated value 4 kV
consumed current maximum 25 mA
protection class IP
? of the enclosure IP40
? of the terminal IP20
shock resistance
? according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 500 Hz: 5g
? for railway applications according to EN 61373 Category 1, Class B
operating period typical 100 000 h
reference code according to IEC 81346-2 P
Substance Prohibitance (Date) 10/01/2014
operating voltage 1
? at AC
- at 50 Hz rated value 24 V
- at 60 Hz rated value 24 V
? at DC rated value 24 V
relative positive tolerance of the operating voltage 20 %
relative negative tolerance of the operating voltage 20 %
Control circuit/ Control
inrush current maximum 2 A
Connections/ Terminals
type of electrical connection screw-type terminals
type of connectable conductor cross-sections
? solid with core end processing 2x (0.5 ... 0.75 mm²)
? solid without co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SU1401-1BB20-1AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.